



ENDURA

COLORED SKIMCOAT

Application Guide:

Substrate Preparation

Surface must be clean, sound and free from foreign materials.
Moisten the substrate using a sponge or cloth before application.

Mixing Instructions

Endura Skimcoat 140-012 is ready-to-use, dampen substrate with clean water before application. Apply evenly until desired thickness is achieved.

Application

Apply mixture using stainless steel knife or trowel. Two or more coats can be applied depending on preferred finish.
Allow to set for 15 mins in between coats. (Depending on weather condition)

Performance Properties:

Pot Life: 1-2 hours
Setting Time: 15-30 mins (depending on weather condition)

VOC Content: Low
Compressive Strength (ASTM C109): 7 days 18-21 MPa
28 days 22-30 MPa

Bond Strength (ASTM 7234): 14 days ≥ 1.00 MPa
28 days ≥ 1.5 MPa

Coverage Area: 20 to 30 sqm /pail (depending on surface condition)

Uses and Advantages:



It can be used on its own to create a complete, visually appealing surface without the need for additional painting. Its adaptability makes it ideal for a variety of decorative finishes, tailored to meet the specific needs and aesthetic goals of the project.

Features:



Interior & Exterior



Excellent Workability



Non Cracking or Flaking



Cost Savings



Can be used as primer

Applications:



Interior Walls



Exterior Facade Application



Precast Concrete



Overhead / Ceiling



Best to use with Endura ToughShield.

Acrylic Water based clear top coat protection for concrete, bricks and natural stone finishes.

Available Colors :

