

Can Leak Tester

CLT

The CLT is an expert at testing various can types, employing a vacuum decay method for quick and accurate detection of both micro and larger leaks, ensuring packaging reliability.

Features:

- Vacuum decay method for different can types.
- FDA-approved flexible membrane.
- Non-destructive detection of micro and larger leaks.



Benefits

Adaptable

Adaptable for metal and composite cans.

Efficient

Quick and efficient testing process.

Protects Integrity

Protects product integrity while testing.

Technical Specifications:

Dimensions and Weight: 580 x 400 x 878 mm, 62 KG

Materials: Powder Coated Steel, Anodized Aluminium, Polycarbonate, Rubber

Power Supply: 100 - 230V 50/60HZ

Air Supply: > 5.5 - < 8 bar/ 8mm connection

Air Consumption: 150 NL/min

Compliance and IP Rating: CE IP40

Leak Detection Method: ASTM F2338

Minimum Leakage: > 0.9 cm³/min

Maximum Testing Capacity: 2P/M

Connections: USB/Ethernet export, 24VDC logic (free programmable)

Packaging Type and Size: Standard can diameters include Ø83 mm, Ø99 mm, Ø127 mm, Ø153 mm

Features: Non-destructive, Accurate, Easy to Operate, Direct Result, Robust Design



Trusted by
1000+
Customers Worldwide

The Zero Waste Foundation

Dedicated To A Greener Tomorrow

Sustainability isn't just a buzzword for us; it's how we operate. Through the Zero Waste Foundation, we're all about doing right by the planet.

From installing machines remotely to cutting down on travel, to choosing recyclable materials and energy-efficient tech, every choice we make is about reducing our footprint and leading the way to a zero-waste future.



Wilgenkade 17, 3992 LL Houten,
The Netherlands



+31 (0)88 – 695 7200



info@oxipack.com