

**Construction Adhesive Kitchen & Bath**

Date of Issue:

08-19-2025

Date of Revision:

08-19-2025

ACCORDING TO US CFR 1910.1200

SECTION 1: IDENTIFICATION**1.1 Product identifier**

Product Name Construction Adhesive Kitchen & Bath
Product Code 115-58A

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified Use(s) Adhesives.
Uses Advised Against Not known.

1.3 Details of the supplier of the safety data sheet

Manufacturer
Company Identification The Gorilla Glue Company
Address of Manufacturer 2101 East Kemper Road
Cincinnati, Ohio
Zip code 45241
Telephone: 513-271-3300
E-mail Info@gorillaglu.com

Supplier
Company Identification The Gorilla Glue Company
Address of Supplier 2101 East Kemper Road
Cincinnati, Ohio
Zip code 45241
Telephone: 513-271-3300
E-mail Info@gorillaglu.com

1.4 Emergency telephone number

Emergency Phone No. 1-800-420-7186
Contact Prosar

SECTION 2: HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture**

US CFR 1910.1200 Skin Sens. 1B :May cause an allergic skin reaction.

2.2 Label elements

According to US CFR 1910.1200
Product Name Construction Adhesive Kitchen & Bath

Hazard Pictogram(s)



GHS07

Signal Word(s)

Warning

Hazard Statement(s)

H317: May cause an allergic skin reaction.



Construction Adhesive Kitchen & Bath

Date of Issue:

08-19-2025

Date of Revision:

08-19-2025

Precautionary Statement(s)

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of water.

P333+P313: If skin irritation or rash occurs: Get medical advice/attention.

P501: Dispose of contents in accordance with local, state or national legislation.

2.3 Other hazards

None known.

2.4 Additional Information

For full text of H/P Statements see section 16.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable.

3.2 Mixtures

HAZARDOUS INGREDIENT(S)	CAS No.	%W/W	Hazard Statement(s)	Hazard Pictogram(s)
Trimethoxyvinylsilane	2768-02-7	1-2	Flam. Liq. 3 H226 Skin Sens. 1B H317 Acute Tox. 4 H332	GHS02 GHS07
N-(3-(trimethoxysilyl)propyl)ethylenediamine	1760-24-3	0.5-1	Skin Sens. 1B H317 Eye Dam. 1 H318 STOT SE 3 H335	GHS05 GHS07
Quartz (SiO ₂)	14808-60-7	0.1-0.2	Not classified	None
3-iodo-2-propynyl butylcarbamate	55406-53-6	<0.1	Acute Tox. 4 H302 Skin Sens. 1 H317 Eye Dam. 1 H318 Acute Tox. 2 H330 STOT RE 1 H372	GHS06 GHS05 GHS08 GHS07
Diocetyl tin oxide	870-08-6	<0.1	STOT SE 2 H371	GHS08
Methanol	67-56-1	<0.02	Flam. Liq. 2 H225 Acute Tox. 3 H301 Acute Tox. 3 H311 Acute Tox. 3 H331 STOT SE 1 H370	GHS02 GHS06 GHS08

For full text of H/P Statements see section 16.



Construction Adhesive Kitchen & Bath

Date of Issue:

08-19-2025

Date of Revision:

08-19-2025

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

Inhalation	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, obtain medical attention.
Skin Contact	Wash with plenty of water. If skin irritation or rash occurs: Get medical advice/attention.
Eye Contact	Flush eyes with water for at least 15 minutes while holding eyelids open. If symptoms persist, obtain medical attention.
Ingestion	Wash out mouth with water. If symptoms develop, obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

Allergic contact dermatitis.

4.3 Indication of any immediate medical attention and special treatment needed

Unlikely to be required but if necessary treat symptomatically.

SECTION 5: FIRE-FIGHTING MEASURES

5.1 Extinguishing Media

Suitable Extinguishing Media	As appropriate for surrounding fire.
Unsuitable Extinguishing Media	None.

5.2 Special hazards arising from the substance or mixture

None anticipated. May decompose in a fire, giving off toxic and irritant vapors.

5.3 Advice for firefighters

Fire fighters should wear complete protective clothing including self-contained breathing apparatus. Dike fire control water for later disposal.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Provide adequate ventilation. Avoid inhalation of vapors. Wear protective equipment to comply with good occupational hygiene practice. Contaminated work clothing must not be allowed out of the workplace. Wash hands and exposed skin after use.

6.2 Environmental precautions

Avoid release to the environment.

6.3 Methods and material for containment and cleaning up

Adsorb spillages onto sand, earth or any suitable adsorbent material. Transfer to a container for disposal.

6.4 Reference to other sections

See Also Section 8, 13.



Construction Adhesive Kitchen & Bath

Date of Issue:

08-19-2025

Date of Revision:

08-19-2025

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

General hygiene measures for the handling of chemicals are applicable. Avoid breathing vapours. Wear protective gloves/protective clothing/eye protection/face protection. Avoid contact with skin. Wash hands and exposed skin after use. Take off contaminated clothing and wash it before reuse. Do not eat, drink or smoke at the work place. If medical advice is needed, have product container or label at hand. Keep out of reach of children.

7.2 Conditions for safe storage, including any incompatibilities

Keep container tightly closed and in a well-ventilated place.

Storage temperature

Ambient.

Storage life

Stable under normal conditions.

Incompatible materials

Strong oxidizing agents.

7.3 Specific end use(s)

Adhesives.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

8.1.1 Occupational Exposure Limits

SUBSTANCE	CAS No.	LTEL (8 hr TWA ppm)	LTEL (8 hr TWA mg/m ³)	STEL (ppm)	STEL (mg/m ³)	Note
Methanol (Methyl alcohol)	67-56-1	200	262	250	328	ACGIH TLV, Skin
Methyl alcohol; methanol	67-56-1	200		250		OSHA PEL, C = 1000ppm
Methanol (Methyl alcohol)	67-56-1	200	260	250	325	NIOSH REL Z-1, (S)
Methanol (Methyl alcohol)	67-56-1	200	260			OSHA PEL Z-1
Silica, crystalline, α-quartz	14808-60-7		0.025			ACGIH TLV, R, A2
Silica, crystalline (respirable dust); Quartz	14808-60-7		0.05			OSHA PEL
Silica, crystalline, α-quartz (Respirable dust)	14808-60-7		0.05			NIOSH REL Z-1, Ca
Silica, crystalline, α-quartz, tripoli (Respirable dust)	14808-60-7		0.05			OSHA PEL Z-1, (z1), (a1)
Silica: CrystallineQuartz (Respirable)	14808-60-7		10			OSHA PEL_Table Z-3, (3d), (3h), (3k), (3l), (3e), (3f)
Tin, organic compounds, as Sn	870-08-6		0.1		0.2	ACGIH TLV, Skin, A4
Tin, organic compounds, as Sn	870-08-6		0.1		0.2	OSHA PEL
Tin, organic compounds (as Sn) (except cyhexatin)	870-08-6		0.1			NIOSH REL Z-1, (S)
Tin, organic compounds (as Sn)	870-08-6		0.1			OSHA PEL Z-1

Remark

Notes

ACGIH TLV

The American Conference of Governmental Industrial Hygienists (ACGIH®) Threshold Limit Values (TLVs®), 2025

Skin

Danger of cutaneous absorption

OSHA PEL

Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs), 2019



SAFETY DATA SHEET

Construction Adhesive Kitchen & Bath

Date of Issue:

08-19-2025

Date of Revision:

08-19-2025

NIOSH REL Z-1	National Institute for Occupational Safety and Health (NIOSH) Recommended Exposure Limits (RELs) from the NIOSH Pocket Guide to Chemical Hazards table Z-1: Up to 10-hour time weighted average (TWA) during a 40-hour work week, 2022
(S)	Danger of cutaneous absorption
OSHA PEL Z-1	Occupational Safety and Health Administration (OSHA) Permissible Exposure Limit (PEL) from 29 CFR 1910.1000 Z-1 Table, 2022
R	Measured as respirable fraction of the aerosol.
A2	Suspected Human Carcinogen
Ca	Potential occupational carcinogens
(z1)	This standard applies to any operations or sectors for which the Respirable crystalline silica standard, 1910.1053, is stayed or is otherwise not in effect.
(a1)	30 mg/m3 (total dust)/% SiO ₂ + 2 OR 250 mppcf (respirable dust)/% SiO ₂ + 5 OR 10 mg/m3 (respirable dust)/% SiO ₂ + 2
OSHA PEL_Table Z-3	Occupational Safety and Health (OSHA) Permissible Exposure Limits (PELs) Table Z-3 Mineral Dusts, 2019
(3d)	250 mppcf (Millions of particles per cubic foot of air, based on impinger samples counted by light-field techniques. Conversion factors - mppcf × 35.3 = million particles per cubic meter = particles per c.c.
(3h)	The percentage of crystalline silica in the formula is the amount determined from airborne samples, except in those instances in which other methods have been shown to be applicable.
(3k)	Both concentration and percentage quartz for the application of this limit are to be determined from the fraction passing through a size-selector with the following characteristics: Aerodynamic diameter (unit density sphere)/ percent passing selector : 2/90; 2.5/75; 3.5/50; 5/25; 10/0. The measurements under this note refer to the use of an AEC (now NRC) instrument. The respirable fraction of coal dust is determined with an MRE; the figure corresponding to that of 2.4mg/m3 for coal dust is 4.5mg/m3.
(3l)	This standard applies to any operations or sectors for which the respirable crystalline silica standard, 1910.1053, is stayed or is otherwise not in effect.
(3e)	The PEL in mg/m3 is calculated by dividing by the percentage SiO ₂ +2.
(3f)	The PEL in mppcf is calculated by dividing by the percentage SiO ₂ +5.
A4	Not Classifiable as a Human Carcinogen

BEI: Biological Exposure Indices (ACGIH)						
Substances	CAS Number	Sampling	Tissues	Control parameters	Biological monitoring guidance value	Comments
Methanol	67-56-1	End of shift	urine	Methanol	15 mg/L	B, Ns

Remark	Notes
B	Background
Ns	Nonspecific

8.2 Exposure controls

8.2.1. Appropriate engineering controls Ensure adequate ventilation. A washing facility/water for eye and skin cleaning purposes should be present.

8.2.2. Personal protection equipment



Eye Protection

Wear protective eye glasses for protection against liquid splashes.



Skin protection

Wear protective clothing and gloves: Impervious gloves.
Breakthrough time of the glove material: refer to the information provided by the gloves' producer.



Respiratory protection

Normally no personal respiratory protection is necessary.
Handling of larger amounts Wear suitable respiratory protection.



Thermal hazards

Not applicable.



Date of Issue:
08-19-2025
Date of Revision:
08-19-2025

Construction Adhesive Kitchen & Bath

8.2.3. Environmental Exposure Controls Avoid release to the environment.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state	Paste.
Color	White.
Odor	Musty.
Melting Point/Freezing Point	Not known.
Boiling point or initial boiling point and boiling range	Not known.
Flammability	Non-flammable.
Lower and upper explosion limit	Not known.
Flash Point	>93.3°C (>200°F)
Auto-ignition temperature	Not known.
Decomposition Temperature	Not known.
pH	Not known.
Kinematic Viscosity	Not known.
Solubility	Solubility (Water) : Insoluble. Solubility (Other) : Not known.
Partition coefficient n-octanol/water (log value)	Not known.
Vapor pressure	Not known.
Density and/or relative density	Density: 1.7 g/cm ³
Relative vapor density	Not known.
Particle characteristics	Not applicable.

9.2 Other information

None.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

None anticipated.

10.2 Chemical Stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No hazardous reactions known if used for its intended purpose.

10.4 Conditions to avoid

Heat and direct sunlight.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

No hazardous decomposition products known.



Construction Adhesive Kitchen & Bath

Date of Issue:

08-19-2025

Date of Revision:

08-19-2025

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity - Ingestion	Calculation method : Not classified. Calculation method : Calculated acute toxicity estimate (ATE) Calc ATE - 360360.38
Acute toxicity - Skin Contact	Calculation method : Not classified. Calculation method : Calculated acute toxicity estimate (ATE) Calc ATE - 2790697.75
Acute toxicity - Inhalation	Calculation method : Not classified. Calculation method : Calculated acute toxicity estimate (ATE) Calc ATE - 299.1 3-iodo-2-propynyl butylcarbamate : ATE : 0.17 mg/l (Dusts/Mists)
Skin corrosion/irritation	Calculation method : Not classified.
Serious eye damage/irritation	Calculation method : Not classified.
Skin sensitization data	Calculation method : May cause an allergic skin reaction. Following a review of the available studies for skin sensitization, it is concluded that Trimethoxyvinylsilane should be classified as skin sensitizer.
Respiratory sensitization data	Calculation method : Not classified.
Germ cell mutagenicity	Calculation method : Not classified. There is no evidence of mutagenic potential.
Carcinogenicity	Calculation method : Not classified. No evidence of carcinogenicity.
Reproductive toxicity	Calculation method : Not classified. No evidence of reproductive effects.
Lactation	Calculation method : Not classified.
STOT - single exposure	Calculation method : Not classified.
STOT - repeated exposure	Calculation method : Not classified.
Aspiration hazard	Calculation method : Not classified.

11.2 Other information

Not known.

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

	Harmful to aquatic life. Harmful to aquatic life with long lasting effects.
Toxicity - Aquatic invertebrates	3-iodo-2-propynyl butylcarbamate Acute : EC50 (48 hour) : 0.645 mg/l Chronic : NOEC (21 days) : 0.0499 mg/l
Toxicity - Fish	3-iodo-2-propynyl butylcarbamate Acute : LC50 (96 hour) : 0.23 mg/l Chronic : NOEC : 0.0084 mg/l
Toxicity - Algae	3-iodo-2-propynyl butylcarbamate EC50 : 5.3 µg/l
Toxicity - Sediment Compartment	Not classified.
Toxicity - Terrestrial Compartment	Not classified.

12.2 Persistence and degradability

No information on this formulation.

**Construction Adhesive Kitchen & Bath**

Date of Issue:

08-19-2025

Date of Revision:

08-19-2025

12.3 Bioaccumulative potential

No information on this formulation.

12.4 Mobility in soil

Insoluble in water. The product is predicted to have low mobility in soil.

12.5 Other adverse effects

None known.

SECTION 13: DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods**

Dispose of this material and its container as hazardous waste. Dispose of empty containers and wastes safely.

13.2 Additional Information

Disposal should be in accordance with local, state or national legislation.

SECTION 14: TRANSPORT INFORMATION**Not classified as hazardous for transport.****14.1 UN number**

Not applicable

14.2 UN proper shipping name

Not applicable

14.3 Transport hazard class(es)

Not applicable

14.4 Packing group

Not applicable

14.5 Environmental hazards

Not classified as a Marine Pollutant.

14.6 Special precautions for user

Not known

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not known

SECTION 15: REGULATORY INFORMATION**15.1 US Federal Regulations**

Toxic and hazardous substances (29 CFR 1910; Subpart Z) Listed : 67-56-1, 14808-60-7

National emission standards for hazardous air pollutants (40 CFR 61.01) Not listed

SARA Title III Section 313 Listed : 67-56-1, 55406-53-6

TSCA (Toxic Substance Control Act) Listed : 2768-02-7 (Active), 67-56-1 (Active), 55406-53-6 (Active), 14808-60-7 (Active), 1760-24-3 (Active), 870-08-6 (Active)

CAA 602 - Ozone Depleting Substances (ODS) Not listed



Construction Adhesive Kitchen & Bath

15.2 US State Regulations

State Right to Know Lists

Proposition 65 (California)	Listed : 67-56-1, 14808-60-7
Massachusetts	Listed : 67-56-1, 14808-60-7
Minnesota	Listed : 67-56-1, 14808-60-7, 870-08-6
New Jersey	Listed : 67-56-1, 14808-60-7, 55406-53-6
Pennsylvania	Listed : 67-56-1, 14808-60-7
Rhode Island	Listed : 67-56-1, 14808-60-7

15.3 Other

OSPAR List of Chemicals for Priority Action	Not listed
OSHA (List of Highly Hazardous Chemicals, Toxics and Reactives)	Not listed
NTP (National Toxicology Program)	Listed : 14808-60-7
IARC (International Agency for Research on Cancer)	Listed : 14808-60-7

SECTION 16: OTHER INFORMATION

The following sections contain revisions or new statements:

1-16

LEGEND

Hazard Pictogram(s)



GHS07

GHS02: GHS: Flame

GHS05: GHS: Corrosion

GHS06: GHS: Skull and crossbones

GHS08: GHS: Health hazard

Hazard classification

Flam. Liq. 2 : Flammable liquid, Category 2
Flam. Liq. 3 : Flammable liquid, Category 3
Skin Sens. 1 : Skin sensitization, Category 1
Skin Sens. 1B : Skin sensitization, Category 1B
Eye Dam. 1 : Serious eye damage/irritation, Category 1
Acute Tox. 2 : Acute toxicity, Category 2
Acute Tox. 3 : Acute toxicity, Category 3
Acute Tox. 4 : Acute toxicity, Category 4
STOT SE 3 : Specific target organ toxicity — single exposure, Category 3
STOT SE 1 : Specific target organ toxicity — single exposure, Category 1
STOT SE 2 : Specific target organ toxicity — single exposure, Category 2
STOT RE 1 : Specific target organ toxicity — repeated exposure, Category 1



Construction Adhesive Kitchen & Bath

Date of Issue:

08-19-2025

Date of Revision:

08-19-2025

Hazard Statement(s)

H225: Highly flammable liquid and vapor.
H226: Flammable liquid and vapor.
H301: Toxic if swallowed.
H302: Harmful if swallowed.
H311: Toxic in contact with skin.
H317: May cause an allergic skin reaction.
H318: Causes serious eye damage.
H330: Fatal if inhaled.
H331: Toxic if inhaled.
H332: Harmful if inhaled.
H335: May cause respiratory irritation.
H370: Causes damage to organs.
H371: May cause damage to organs.
H372: Causes damage to organs through prolonged or repeated exposure.

Precautionary Statement(s)

P261: Avoid breathing vapours.
P272: Contaminated work clothing must not be allowed out of the workplace.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352: IF ON SKIN: Wash with plenty of water.
P321: Specific treatment (see Medical Advice on this label).
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P362+P364: Take off contaminated clothing and wash it before reuse.
P501: Dispose of contents in accordance with local, state or national legislation.

Acronyms

ATE : Acute Toxicity Estimate
CAS : Chemical Abstracts Service
LTEL : Long term exposure limit
STEL : Short term exposure limit
STOT : Specific Target Organ Toxicity

Key literature references and sources for data used to compile the SDS

US CFR 1910.1200

Disclaimers

Information contained in this publication or as otherwise supplied to Users is believed to be accurate and is given in good faith, but it is for the Users to satisfy themselves of the suitability of the product for their own particular purpose. The Gorilla Glue Company gives no warranty as to the fitness of the product for any particular purpose and any implied warranty or condition (statutory or otherwise) is excluded except to the extent that exclusion is prevented by law. The Gorilla Glue Company accepts no liability for loss or damage (other than that arising from death or personal injury caused by defective product, if proved), resulting from reliance on this information. Freedom under Patents, Copyright and Designs cannot be assumed.