

## SIROCCO PINHOLE



RECYCLED  
CONTENT



FIRE  
PERFORMANCE




BIO-SOLUBLE  
(NOTE Q)



100%  
ASBESTOS-FREE



25 YEAR  
WARRANTY

<b>MATERIAL</b>	Mineral Fibre
<b>SURFACE</b>	Perforated, sand textured face
<b>PATTERN</b>	Non directional pattern design
<b>FACE FINISH</b>	

<b>COLOURS</b>	 															
<b>ENVIRONMENT</b>	ISO 14001 and ISO 9001															
<b>RECYCLED %</b>	60% recycled content															
<b>FIRE RATING</b>	NCC GROUP 1 (ISO 9705:2016)															
<b>PERFORMANCE</b>	<table border="1"> <thead> <tr> <th>Thickness</th> <th>NRC</th> <th>CAC</th> <th>LRV</th> <th>RH</th> </tr> </thead> <tbody> <tr> <td>15mm</td> <td>0.55</td> <td>35</td> <td>0.86</td> <td>99</td> </tr> <tr> <td>19mm</td> <td>0.65</td> <td>40</td> <td>0.86</td> <td>99</td> </tr> </tbody> </table>	Thickness	NRC	CAC	LRV	RH	15mm	0.55	35	0.86	99	19mm	0.65	40	0.86	99
Thickness	NRC	CAC	LRV	RH												
15mm	0.55	35	0.86	99												
19mm	0.65	40	0.86	99												

### SIZE GUIDE

**Note:** more module and size options available.

#### APOLLO TWO-WAY TOP HAT GRID

MODULE	LENGTH	WIDTH	C SPLINE
1200mm	1188mm	396mm / 3 Tiles	25mm
	1188mm	297mm / 4 Tiles	25mm
	1188mm	237.6mm / 5 Tiles	25mm
1350mm	1338mm	446mm / 3 Tiles	35mm
	1338mm	334.5mm / 4 Tiles	25mm
	1338mm	267.6mm / 5 Tiles	25mm
1500mm	1488mm	496mm / 3 Tiles	35mm
	1488mm	372mm / 4 Tiles	35mm
	1488mm	297.6mm / 5 Tiles	25mm


#### APOLLO ONE-WAY TOP HAT GRID

MODULE	LENGTH	WIDTH	C SPLINE
1200mm	1188mm	600mm max.	25mm
1350mm	1338mm	450mm max.	25mm / 35mm
1500mm	1488mm	500mm max.	25mm / 35mm


#### APOLLO T-BAR GRID

MODULE	LENGTH	WIDTH	T BAR
1200x600mm	1195mm	595mm	15mm / 24mm
600x600mm	595mm	595mm	


### EDGE DETAILS




Top Hat Grid  
with c-spline edge  
**Ref: CS**



Top Hat Grid  
with square edge  
**Ref: SQ**



T-Bar Grid  
with square edge  
**Ref: SQ**



15mm T-Bar Grid  
with tegular edge  
**Ref: TG15**



24mm T-Bar Grid  
with tegular edge  
**Ref: TG24**