

## ASTRID



RECYCLED  
CONTENT



FIRE  
PERFORMANCE



BIO-SOLUBLE  
(NOTE Q)



100%  
ASBESTOS-FREE




25 YEAR  
WARRANTY

**MATERIAL** Mineral Fibre

**SURFACE** Latex paint with perforated face

**PATTERN** Non directional pattern design

**FACE FINISH**



**COLOURS**

**ENVIRONMENT** ISO 14001 and ISO 9001

**RECYCLED %** 45% recycled content

**FIRE RATING** NCC GROUP 1 (ISO 9705:2016)

**PERFORMANCE**

Thickness	NRC	CAC	LRV	RH
15mm	0.60	35	0.86	99
19mm	0.70	40	0.86	99

### SIZE GUIDE

**Note:** more module and size options available.

#### APOLLO TWO-WAY TOP HAT GRID

MODULE	LENGTH	WIDTH	C SPLINE
1200mm	1188mm	396mm / 3 Tiles	25mm
	1188mm	297mm / 4 Tiles	25mm
	1188mm	237.6mm / 5 Tiles	25mm
1350mm	1338mm	446mm / 3 Tiles	35mm
	1338mm	334.5mm / 4 Tiles	25mm
	1338mm	267.6mm / 5 Tiles	25mm
1500mm	1488mm	496mm / 3 Tiles	35mm
	1488mm	372mm / 4 Tiles	35mm
	1488mm	297.6mm / 5 Tiles	25mm


#### APOLLO ONE-WAY TOP HAT GRID

MODULE	LENGTH	WIDTH	C SPLINE
1200mm	1188mm	600mm max.	25mm
1350mm	1338mm	450mm max.	25mm / 35mm
1500mm	1488mm	500mm max.	25mm / 35mm


#### APOLLO T-BAR GRID

MODULE	LENGTH	WIDTH	T BAR
1200x600mm	1195mm	595mm	15mm / 24mm
600x600mm	595mm	595mm	


### EDGE DETAILS




Top Hat Grid  
with c-spline edge  
**Ref: CS**



Top Hat Grid  
with square edge  
**Ref: SQ**



T-Bar Grid  
with square edge  
**Ref: SQ**



15mm T-Bar Grid  
with tegular edge  
**Ref: TG15**



24mm T-Bar Grid  
with tegular edge  
**Ref: TG24**