

MEDISHIELD



RECYCLED
CONTENT



FIRE
PERFORMANCE



BIO-SOLUBLE
(NOTE Q)



100%
ASBESTOS-FREE



25 YEAR
WARRANTY

MATERIAL Mineral Fibre Laminated with Transparent Acoustic Tissue

SURFACE Advanced antibacterial properties

PATTERN Non directional pattern design

FACE FINISH



COLOURS

ENVIRONMENT ISO 14001 and ISO 9001

RECYCLED % 72% recycled content

FIRE RATING NCC GROUP 1 (ISO 9705:2016)

PERFORMANCE	Thickness	NRC	CAC	LRV	RH
	15mm	0.65	35	0.90	95
	19mm	0.70	40	0.90	99

SIZE GUIDE

Note: more module and size options available.

APOLLO TWO-WAY TOP HAT GRID

MODULE	LENGTH	WIDTH	C SPLINE
1200mm	1188mm	396mm / 3 Tiles	25mm
	1188mm	297mm / 4 Tiles	25mm
	1188mm	237.6mm / 5 Tiles	25mm
1350mm	1338mm	446mm / 3 Tiles	35mm
	1338mm	334.5mm / 4 Tiles	25mm
	1338mm	267.6mm / 5 Tiles	25mm
1500mm	1488mm	496mm / 3 Tiles	35mm
	1488mm	372mm / 4 Tiles	35mm
	1488mm	297.6mm / 5 Tiles	25mm


APOLLO ONE-WAY TOP HAT GRID

MODULE	LENGTH	WIDTH	C SPLINE
1200mm	1188mm	600mm max.	25mm
1350mm	1338mm	450mm max.	25mm / 35mm
1500mm	1488mm	500mm max.	25mm / 35mm


APOLLO T-BAR GRID

MODULE	LENGTH	WIDTH	T BAR
1200x600mm	1195mm	595mm	15mm / 24mm
600x600mm	595mm	595mm	


EDGE DETAILS




Top Hat Grid
with c-spline edge
Ref: CS



Top Hat Grid
with square edge
Ref: SQ



T-Bar Grid
with square edge
Ref: SQ



15mm T-Bar Grid
with tegular edge
Ref: TG15



24mm T-Bar Grid
with tegular edge
Ref: TG24