

TEST REPORT

No.: CZFTS25000395R02_EN

Date: Sep 09,2025

Page 1 of 4

ENTERPRISE INDUSTRIES AUSTRALIA PTY LTD.

Suite 99/26-32 Pirrama Road Pymont ,Australia NSW 2009

Sample Description : e-Mineral-Elegant: Fibreglass ceiling
Color : white
Thickness : 20mm
Composition : fiberglass
Density : 90 kg/m³
Client Reference Info : e-Mineral, Elegant

The above sample(s) data and information was / were submitted and identified on behalf of the client. SGS is not responsible for the authenticity, integrity and results of the data and information and / or the validity of the conclusion arising therefrom. Results apply to the sample as received.

Sample Receiving Date : Aug 12,2025
Testing Period : Aug 12,2025 to Aug 22,2025
Test Required : AS 5637.1:2015 Determination of fire hazard properties.
 And the test method is according to AS ISO 9705-2003 (R2016) Fire tests
 – Full-scale room test for surface products.
Test result(s) : See attached sheet

Signed for and on behalf of
 SGS-CSTC Standards Technical Services (Changzhou) Co., Ltd.

Bruce Zhu

Bruce Zhu
 Approved signatory



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

Test Requested:

AS 5637.1:2015 Determination of fire hazard properties.

And the test method is according to AS ISO 9705-2003 (R2016) Fire tests – Full-scale room test for surface products.

I. Sample details


Sample description	Fibreglass ceiling
Color	White
Area Density(kg/m ²)	1.8
Sample size	600mm*600mm
Thickness (mm)	20 mm

II. Preparation and mounting of test specimens

Installation Guidance for Test Materials

1. Installation instructions for the ceiling part:

Figure 1: Ceiling Part



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

2. Installation instructions for the wall part:




Figure 2: Wall Part (2.4m)




Figure 3: Wall Part (3.6m)



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

III. Test conducted

The fire test was conducted in accordance with AS ISO 9705-2003(R2016) Fire tests – Full-scale room test for surface products, and the report **No. CZFTS25000395R01_EN**.

IV. Conclusion

According to Assigning group numbers requirements, the sample assigned as **Group 1**.

SMOGR_{RC}=1.03m²/s² x 1000

Assigning group numbers (According to AS 5637.1:2015 clause 4.2)

- (a) Group 1—material that does not reach flashover when exposed to 100 kW for 600 s followed by exposure to 300 kW for 600 s.
- (b) Group 2—material that reaches flashover following exposure to 300 kW within 600 s after not reaching flashover when exposed to 100 kW for 600 s.
- (c) Group 3—material that reaches flashover in more than 120 s but within 600 s when exposed to 100 kW.
- (d) Group 4—material that reaches flashover within 120 s when exposed to 100 kW.

Statement :

The test results relate only to the behaviour of the test specimens of a material under the particular conditions of the test; they are not intended to be the sole criterion for assessing the potential fire hazard of the material in use.

Within the territory of the People's Republic of China, this report is only used for domestic customers' scientific research, teaching, internal quality control and product R & D, and does not have the role of social certification. The test results or test reports shall not be used for improper or illegal publicity.

End of Report



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com