



ENHANCED PIPE DETECTION TOOL (ePDT)


The enhanced Pipe Detector Tool (ePDT) is a two-inch O.D. advanced ferromagnetic metal thickness evaluation instrument. The integrity of multiple concentric tubulars strings can be evaluated in-situ. In most cases, this eliminates pulling the production tubing string, or disassembling the surface completion hardware to facilitate data acquisition.

ePDT, is GOWELL's Next Generation thickness instrument. It is based on evolutionary pulsed eddy current physics which permits quantitative thickness measurements for up to five concentric pipes. The state-of-the-art instrument includes a new patented antenna that significantly improves measurement capabilities. This allows evaluation of tubulars ranging from 2-7/8-inch to 26-inch O.D

FEATURES & APPLICATIONS

- Warrior™ acquisition system compatible
- 2-inch O.D. - deployed centralized
- Clear real-time visualization for QC and onsite evaluation
- Combinable with all Pegasus Series Tools
- Quantitative 4 to 5 pipe thickness evaluation (dependent on total metal thickness)
- Pre-job planner software that combines a powerful forward modeling module and simulation tool
- Proprietary post-processing module built-in to ViewWell™ Well Integrity Platform
- Simultaneously assess metal thickness of multiple tubulars strings
- Locate collars and shoes of concentric strings
- Aid P&A risk management by determining integrity of adjacent strings
- Determine tubulars condition prior to workovers or re-fracs
- Verify condition of casing patches and patched casing.
- Establish trend-lines for tubulars degradation over time
- Pin-point leak source location by combining with ANT, MFC, RBL, PLT, etc

91.2 in
(2317 mm)





ENHANCED PIPE DETECTION TOOL (EPDT)

The ePDT is fully combinable with GOWELL's Pegasus instruments, including Multi-Finger Imaging Calipers (MFC), Array Noise Tool (ANT), Production Logging Tools (PLT) and our Digital Radial Bond Tool (RBL). The combination yields a comprehensive evaluation of well integrity, providing accurate thickness information for multiple pipe strings as well as leak detection, multi-phase fluid flow and cement bond quality.

During real-time logging via Warrior™ the software provides a comprehensive wellsite quality control display which offers clear visual indication of tool performance and pipe conditions. Post processing is performed with GOWELL's proprietary module contained in the industry leading Well Integrity Evaluation Platform - ViewWell™. When using ViewWell, all MFC, ePDT and Passive Noise data can be processed, viewed and interpreted side-by-side within a single software platform.

SPECIFICATIONS

EPDT
P/N 100520560

GENERAL SPECS

Maximum Diameter	51 mm (2.0 in)
Temperature Range	-20 to 175° C (-4 to 350° F)
Maximum Hydrostatic Pressure	138MPa (20kpsi)
Overall Length	2317 mm (91.2 in)
Makeup Length	2288 mm (90.1 in)
Weight	65lbs
Maximum Total Pipe Wall Thickness	92 mm (3.6 in)
Measurement Range	60 to 609.6 mm (2.362 to 24 in)
Recommended Logging Speed	1.5 to 9.1 m/min (5 to \$30~ft/min) \$
Working Voltage	150V-300V

First (A) Pipe Measurement

Maximum A Pipe Wall Thickness	25.4 mm (1.0 in)
Thickness Repeatability	0.16 mm (0.006 in) or +/- 0.6% of Thickness
Accuracy	+/-5%
A Pipe (2-7/8") Minimum detectable fault	12.7 mm (0.5")

Second (B) Pipe Measurement

Maximum B Pipe Wall Thickness	25.4 mm (1.0 in)
Thickness Repeatability	0.46 mm (0.018 in) or +/- 1.8% of Total Thickness
Accuracy	+/-8%
B Pipe (2-7/8"+7) Minimum detectable fault	38.1 mm (1.5 in)

Third (C) Pipe to Fifth (E) Pipe Measurement

Maximum C, D, E Pipe Wall Thickness	25.4 mm (1.0 in) max per pipe
Thickness Repeatability	1.27 mm (0.05 in) or +/- 5% of thickness
Accuracy	+/-12%
C, D, E Pipes (2-7/8+7+13-3/8") Min. detectable fault	76.2 mm (3 in)

Measurement Point (From the shoulder of lower split ring to the mid-point of sensor)

Sensor	53.52 cm (21.07")
--------	-------------------