

## MODEL T03-1800

Special calender for pieces or continuous fabrics, used for:

- Transfer printing
- Direct inks reactivation
- Thermosetting - heatsetting

Versatile and polyvalent calender, developed for transfer printing of all the follows work conditions, according to required options:

- Printing paper in roll and material to be printed in roll
- Printing paper in roll and material to be printed in pieces
- Printing paper in sheets and material to be printed in pieces

### 1. CHARACTERISTICS OF HEATING CYLINDER:

- 1.1. Diameter : 350 mm (13,78").
- 1.2. Width : 1.800 mm (70,87").
- 1.3. Working Width: 1.650 mm (65")

### 2. HEATING SYSTEM AND TEMPERATURE CONTROL:

- 2.1. The cylinder is heated by one resistor (heating element) in a vacuum sealed oil bath, in complete absence of air and pressure. MONTI ANTONIO S.p.a system.
- 2.2. The temperature of the cylinder is set by the touch screen and regulated by an electronic sheet. The temperature control is equipped with an alarm system and a limitation system of maximum temperature (230 °C).

### 3. TENSION CONTROLS:

- 3.1. Tension control for printing material in roll:
  - Entry: axial unwinding with manual brake
  - Exit: winding per contact with roll in exit
- 3.2. Tension control for printing paper in roll:
  - Entry: axial unwinding with disk brake with pneumatic adjustment
  - Exit: axial motorised winding with pneumatic device for motion transmission from the main motor
- 3.3. Tension control for protection paper:
  - Entry: axial unwinding with disk brake with pneumatic adjustment
  - Exit: axial motorised winding with pneumatic device for motion transmission from the main motor

### 4. OTHER DEVICES INTO MACHINE:

- 4.1. Short front working table, 800 mm
- 4.2. Single motor
- 4.3. NOMEX felt with tension adjustment system and automatic felt-centring device
- 4.4. Incorporated system of felt protection in case of black out and/or compressed air lack
- 4.5. Meter-counter, with alarm to predetermine the length of production runs
- 4.6. General management of the machine, including temperature control by adjustable PLC for the memorization of production data
- 4.7. Front touch-screen keyboard for production data access and programming

### 5. ROLLS DIAMETER MACHINE WITHOUT OPTIONS:

- Fabric roll diameter in entry 300 mm (11,81").
- Fabric roll diameter in exit 300 mm (11,81").
- Printing paper roll diameter in entry 250 mm (9,84") - Larger diameters on request.

All data and technical features are purely indicative, subjected to changes without prior notice and refer to standard machines without options

## MODEL T03-1800

- Printing paper roll diameter in exit 250 mm (9,84") - Larger diameters on request.
- Protection paper roll diameter in entry 300 mm (11,81").
- Protection paper roll diameter in exit 300 mm (11,81").

### 6. TECHNICAL DATA:

- 6.1. Installed power: 19,67 kW
- 6.2. Average electric consumption: 13,37 kW/h
- 6.3. Compressed air pressure: 4-8 bar
- 6.4. Mechanic speed: 0.3 - 4 m/min
- 6.5. Overall dimensions (with front table): width 3.210 mm (126,38"). length 2.440 mm (96,10"). height 1.625 mm (63,98").
- 6.6. Net weight: 1.800 kg
- 6.7. Machine produced according to CE rules
- 6.8. Customs tariff: 84 51 80 30



**Headquarter (India) : DCC Print Vision LLP,**

802, Kamla Executive Park, Opp. Vazir Glass Work, Off. M.V. Road, J. B. Nagar,  
Andheri (East), Mumbai- 400 059, India. Tel. : +91 022 4085 5000



+91 9930 200 400



marketing@groupdcc.com



www.groupdcc.com



**OUR FOOTPRINTS : TIRUPPUR**

+91 93630 21265

**BANGLADESH**

+88 01714220088

**LUDHIANA**

+91 98719 88775

**KOLKATA**

+91 98314 72212

**BENGALURU**

+91 95855 44265

**DELHI**

+91 98719 88775

**SURAT**

+91 86575 90290