

CLING 6 WS

Data Sheet

CLING 6WS

Elevate Your Ambiance

The **CLING 6WS** is a versatile active ceiling speaker crafted for both commercial and household environments. It features a striking bright blue paper cone and an ultra-narrow frameless magnetic grille that delivers a modern, stylish appearance while ensuring exceptional affordability.



Integrated PoE++ & Advanced Networking

The speaker features high-quality 2-way coaxial drivers and supports PoE++ or an optional DC24V supply for clean, single-cable installation. It offers WiFi and LAN connectivity with AirPlay, DLNA, and QPlay streaming, while its built-in digital amplifier delivers clear, high-quality sound with reliable, low-latency performance.

Durable Design & Flexible Control

Application: Ideal for boutique hotels, luxury homes, fine dining venues, luxury retail spaces, museums & galleries, and VIP lounges, the **CLING** series delivers the perfect balance of premium performance, refined style, and cost-effectiveness.

Technical Specifications

Unit	CLING 6WS
Rated Power:	30W
Line Input:	48V PoE++ (IEEE802.3bt)/DC24V
Impedance:	8Ω
Sensitivity (1w,1m):	88dB
Frequency Response:	55Hz~22kHz (-10dB)
Amplifier Output Power:	60W (2x 30W)
Amplifier Frequency Range:	20Hz~20kHz
Max Sensitivity:	112dB
Material:	ABS Shell, Magnetic Grille
Colour:	Front Cover: White; Rear Barrel: Black
Operating Temperature / Humidity:	-25°C~+55°C; <95 %
Speaker Unit:	6.5" Woofer + 1" Tweeter
Dimensions (LxH):	Ø 265x205mm
Cutout Size:	Ø 230mm
Net Weight:	4.2kg
Mounting Type:	4 tClaw Rotating Mounting Ears
Audio Input:	Bluetooth 5.0, AUX IN

Technical Specifications

Unit	CLING 6WS
Network Connectivity:	WiFi 2.4G, LAN
Music Streaming Protocols:	Airplay, DNA, QPlay, etc
Audio Format Support:	MP3, AAC, FLAC, ALAC, WMA, APE, WAV, OGG, etc.
Music Source Services:	Tunein, HeartRadio, TIDAL, Napster, Qobuz, etc.
Power Dissipation:	≤100W
IP Rating:	IEC529 IP55 Compliant

Contact Us

info@bataudio.com
www.bataudio.com
United Kingdom

