

EU Declaration of Conformity / UKCA
A 2116 .. / ..(colour)

 EU Declaration of Conformity

Adapter



Order No. A 2116 .. / ..(colour)

Manufacturer Schützinger GmbH | Eichwiesenring 6 | 70567 Stuttgart | Germany

The sole responsibility for issuing this declaration carries the manufacturer.

Rated voltage 1000 V CAT II

Rated current 32 A

Description of the product The safety adapter can be fitted into all Ø 4 mm sockets. This ensures compatibility with safety measuring leads with rigid sleeves. By screwing a locking screw (SW 1.5) into the splay plug, the safety adapter can be tightly connected to the Ø 4 mm socket. The safety adapter can then no longer be removed without tools.

European directives and European regulations The object of the declaration described above is in conformity with the relevant harmonization legislation of the Union:

- *Low Voltage Directive 2014/35/EU*
published on 29 March 2014 at the EU Official Journal L 96/357-374 Number
- *RoHS II-Directive 2011/65/EC*
published on 01 July 2011 at the EU Official Journal L 174/88 Number
Applied exemption, Annex III, 6c: copper alloy containing up to 4 % lead by weight
- *Commission delegated Directive 2015/863/EC*
published on 06 June 2015 at the EU Official Journal L 137/10 Number
- *REACH-Regulation No. 1907/2006*
published on 30 December 2006 at the EU Official Journal L 396/1 Number, note:
CAS-Number: 7439-92-1
Description: lead, up to 3 %, contained in metal parts

Applied harmonized standards and technical specifications

- *IEC/EN 61010-1:2011-07*
Safety requirements for electrical equipment for measurement, control and laboratory use - Part 1: General requirements (IEC 61010-1:2010 + Cor.: 2011)

EU Declaration of Conformity / UKCA
A 2116 .. / ..(colour)

Stuttgart, 25.02.2025


.....
Bernhard Schützinger, CEO

EU Declaration of Conformity / UKCA
A 2116 .. / ..(colour)



Adapter

Order No.	A 2116 .. / ..(colour)
Manufacturer	Schützing GmbH Eichwiesenring 6 70567 Stuttgart Germany
The sole responsibility for issuing this declaration carries the manufacturer.	
Rated voltage	1000 V CAT II
Rated current	32 A
Description of the product	The safety adapter can be fitted into all Ø 4 mm sockets. This ensures compatibility with safety measuring leads with rigid sleeves. By screwing a locking screw (SW 1.5) into the splay plug, the safety adapter can be tightly connected to the Ø 4 mm socket. The safety adapter can then no longer be removed without tools.
UK Statutory requirements	The product is in conformity with the relevant UK Statutory Instruments (and their amendments): <ul style="list-style-type: none">• <i>The Electrical Equipment (Safety) Regulations 2016</i>• <i>The Restriction of the Use of certain hazardous substances in Electrical and Electronic Equipment Regulations 2012</i>

Stuttgart, 25.02.2025



.....

Bernhard Schützing, CEO