



FOR NEW EQUIPMENT SALES, CALL
866.966.2969
TO SPEAK WITH AN ALTEC REPRESENTATIVE
or visit us online at altec.com

 **Altec**
TELESCOPIC CRANE

STANDARD FEATURES

- Altec LMAP (Load Moment & Area Protection) System
 - » Rated Capacity Limiter
 - » Displays: Boom Length, Boom Angle, Load on Hook, Percent of Rated Capacity
 - » Operator Defined Audible Alarm Set-Points for Boom Angle, Length and Rotational Position
- Dual Entry 20° Tilt Cab with Heater and A/C
- Outrigger Boom Interlock System
- Outrigger Motion Alarm
- Winch Drum Rotation Indicator
- Anti-Two Block Device
- Winch Control at Load Hook Stow Point
- Hydraulic Oil Cooling System
- Front Bumper Outrigger
- 15,000 lb 2-Speed High-Performance Piston Winch
- Rotation Resistant Wire Rope

OPTIONS

- ASME B30.23 Personnel Lifting Package
 - » 2-Man, Steel Platform
 - Fixed, 800 lb (362.8 kg) Capacity, or
 - Rotating, 1,200 lb (544.3 kg) Capacity
 - » Radio Remote Controls
 - » Fall Protection
- ASME B30.23 Compliant Test Weight Package
- 1-Piece 31 ft (9.4 m) Jib
- 2-Piece 55 ft (16.8 m) Jib, 31 ft (9.4 m) Retracted
- Rotating Front Bumper Outrigger
- Load Block and Ball Storage on Deck of Crane
- Auxiliary Hoist
- Glide Swing
- Emergency 12V DC Lowering System

CRANE SPECIFICATIONS

Maximum Lift Capacity	76,000 lb (34,475 kg)
Boom Length (5-Section)	127 ft (38.7 m)
Powered Sheave Height	137 ft (41.8 m)
Maximum Sheave Height with 2-Stage Jib	192 ft (58.5 m)
Stowed Travel Height	12.9 ft (3.9 m)
Vehicle Travel Length	38 ft (11.6 m)
3 Position Out-and-Down Outriggers	
Full Span	24 ft (7.3 m)
Mid Span	15.8 ft (4.8 m)
Short Span	8.17 ft (2.5 m)
Control System	Pilot-Operated, Hydraulic
ASME B30.5 Compliant	

LOAD MOMENT AND AREA PROTECTION



The convenient LMAP menu navigation with an intuitive user interface displays load on hook, rated capacity percentage, boom length and angle, load radius, and operator-defined protection with audible alarms. While the intuitive display and user interface are unique to Altec, the system's hardware consists of common "off-the-shelf" components that were critically selected for their performance and serviceability.

UNIT		RECOMMENDED CHASSIS DIM				MINIMUM RECOMMENDED CHASSIS SPECIFICATIONS				
Model	Rear Axle	CA (in)	WB (in)	AF (in)	AS (in)	Front Axle Rating (lb)	Rear Axle Rating (lb)	GVWR (lb)	Frame Sec Modulus (in ³)	Frame RBM (in-lb)
AC38-127S	Tandem w/ Pusher	205	292	100	54	20,000	44,000	64,000	consult factory	
AC38-127S	Tri-Drive	201	288	120	54	20,000	60,000	80,000	consult factory	



866-966-2969
sales@altec.com

AIOSAC38127S-1217-v1-r1

33 Inverness Center Parkway
Birmingham, AL 35242
Fax 205.449.4774
www.altec.com

For more complete information on Altec products and services, visit us on the web at www.altec.com.

© 2017 Altec Inc
All Rights Reserved

Material and specifications are subject to change without notice. Featured units in photos may include optional features. Please contact an Altec representative for all available options. Charts published herein are intended to be a guide only and should not be construed to warrant application for lifting purposes. Consult supplied operation manual for further details.

Altec® and the Altec logo are registered trademarks of Altec Inc in the United States and various other countries and may not be used without permission.

