



# XECO600

Line Conditioner



UL 810  
CSA C22.2 No. 190  
EN 61000-6-3:2007  
EN 61000-6-1:2007  
EN 61439-1:2011

XECO600 Electrical Rating	
Voltage Rating	480 V
Current Rating	30 A
Frequency	50/60 Hz
Phase	3-Phase
Hybrid Network	
Voltage Rating	600 VAC
Capacitance	25 $\mu$ F
Frequency	50/60 Hz
Short-Circuit / Interrupt Rating	10,000 AFC
Temperature Rating	85°C
Terminal Block	
Voltage Rating	600 VAC
Current Rating	60 A
Accepted Conductor Sizes	8 AWG and 14 AWG
Number of Circuits	3
Internal Supply Wiring (Branch-Circuit Connection)	
Voltage Rating	600 VAC
Conductor Size	8 AWG
Wire Type	AWM
Temperature Rating	90°C
Length Provided	36" minimum
Internal Wiring (Hybrid to PWB)	
Voltage Rating	600 V
Conductor Size	14 AWG
Temperature Rating	90°C minimum
Compliance / Listing	UL / CSA
PCB (PWBs)	
Material Type	Type 501
Flammability Rating	94V-0
Temperature Rating	130°C
Compliance / Listing	UR, CSA
Characteristics	
Dimensions	425 x 410 x 82.5 mm
Weight	6.40 kg
Enclosure Type	Power-coated sheet metal (1.2 mm)