



X3 series

Temperature recorders for cold chain compliance.

VIACHAIN's temperature recorders enable temperature monitoring and proof of compliance from origin to destination for food, pharmaceuticals and other temperature-controlled cargo.

As part of a comprehensive cold chain telematics solution that includes sensors, connectivity and the ColdChainView web application, the X3 series delivers printed or electronic temperature records, real-time event-based alerts, advanced reports and analytics, geofences and more.

Available in two configurations:

- TX3: rugged case for installation outdoors
- RX3: compact for installation inside the cabin

Regulatory compliance

VIACHAIN's X3 series meets the highest requirements of local and international regulations and guidelines for the transportation of food and pharmaceuticals—GAMP 5 (Good Automated Manufacturing Practice established by the pharmaceutical industry), HACCP (food safety), EN12830:2018 Class 0.5, CE, RED and PTCRB.

Feature-rich

The temperature recorders feature an integrated printer, a large display, an easy-to-use interface, multi-language support, a built-in accelerometer and more. In addition to on-demand printed temperature records, The

Proof of cold chain compliance

Integrated printer

Easy to use and install

Event-based alarms

Multi-temperature compartment support

RX3 gives drivers access to status reports right from the cabin.

Access real-time and historical reports and run analytics on asset performance, utilization and status to increase operational visibility, enable more efficient business planning and gain a better return on investment. Receive and manage temperature, intrusion, geofence and maintenance

alerts in real-time through the built-in display or the ColdChainView application to ensure timely corrective measures are taken.

The X3 series supports up to 6 sensors, making it ideal for multicompartment trailers with different temperature requirements. VIACHAIN's X3 series is compatible with refrigerated units from most manufacturers.

Compatible refrigeration systems

- Carrier
- Thermo King
- Mitsubishi
- Konvekta

Operating voltage

- 10 - 32 V with load dump protection

Power

- Consumption: nominal value 0.6 W, max. 25 W (while printing)
- Low power mode capability

Environmental

- Operating temperature: -30 °C / +70 °C
- Maximum temperature: -40 °C / +85 °C
- TX3: IP65
- RX3: IP20

Humidity

- Relative humidity: 97% at 25 °C

Memory size

- Memory size: 8 MB, minimum 1 year with 2 sensors on a 15 min logging interval

Interfaces

- Inputs: 6 temperature sensors (-50 °C / +70 °C)
- Digital inputs: 1 digital for display background light, active >5 VDC, 4 closed circuit
- Open output: 1 switched to ground and current limited to 1A
- 3-axis accelerometer

Bluetooth

- Data transmission to EuroTool service software and service/parameter programming via Bluetooth
- External interfaces
- Data ports: 2 RS-232 connectors for external devices
- CAN Bus: 1 port

Cellular communications

- 3G HSPA

Dimensions

- TX3: 225 x 185 x 111,7 mm (8.86" x 7.28" x 4.4")
- RX3: 186 x 58 x 150 mm (7.32" x 2.28" x 5.91")

Compliance

- EN 13486, CLASS 1
- 852/2004 AS OF 1.1.2006
- HACCP
- GAMP 5
- CE
- RED
- PTCRB

Certification

- EN12830:2018 Class 0.5 (-25°C to +7°C), Class 1 (-40°C to +50°C)
- E-13 type approval to 95/54/EEC



Although we strive to ensure accuracy in all of our published specifications, actual field performance can vary depending on a variety of environmental, installation and usage factors, as well as third-party factors such as cellular providers. The specifications listed are approximations, and do not constitute binding statements or modify the terms and conditions of purchase or lease including, but not limited to, product operational limitations and warranties. All specifications are subject to change without notice. Please check www.viachain.io to ensure you have the latest version of these specifications.

For more on our solutions or to book a demo, email us: sales@viachain.io

Visit our website www.viachain.io

VIACHAIN, an ORBCOMM company, is a global leader in IoT solutions that deliver enhanced sustainability, cargo safety and operational reliability for logistics providers, trucking fleets and the world's largest shipping lines. Our pioneering technology transforms intermodal containers and trailers into smart assets to optimize efficiency and reduce risk. Providing real-time visibility and insights into location, condition, safety and route performance, our solutions enable fast reactions to disruptions. With more than 1.6 million connected assets, VIACHAIN is where IoT powers smart supply chains.