



Technical Data

Model

VELOCITI-NMC-5139



High Performance & Long Life

Delivers over 1000 cycles at 100% Depth of Discharge (DoD), consistent power with low degradation rate

Environment & Safety Focused

IP67 rated- complete protection against dust and solids ingress and is protected against the effects of immersion in water, protection from thermal runaway.

Robust & Compact Design

Enclosure: Al 6063 (Extrusion)

Connectors: SB50

Battery Management System (BMS)

14S50A intelligent BMS, real-time protection against overcharge, over-discharge, short circuit, temperature spikes, and thermal runaway,

Additional features

IoT for real time tracking



Main Parameter		
Battery Chemistry		NMC
Capacity (Ah)		39
Nominal Voltage (V)		50.4
Operating Voltage (V)		35-58.8
Nominal Energy (kWh)		1.96
Usable Energy (kWh)		1.96
Charge/Discharge Current (A)	Recommended	+19.5/-19.5
	Max.	+19.5/-39
	Peak(25°C)	+19.5/-39
Other Parameter		
Recommended Depth of Discharge		100%
Dimension (L*W*H, mm)		188 x 156 x 379
Weight Approximate(kg)		18
IP Rating of Enclosure		IP67
Operating Temperature		0-55
Recommend Operating Temperature (°C)		Charge: 0-55, Discharge: -10-60
Storage Temperature		At 30% SOC, 25-45°C
Humidity		90% RH
Altitude		<2000 m
Cycle Life		1000
Installation		E-2W
Warranty Period		2 years
Energy delivered over lifetime (kWh)		1560

DC Usable Energy test conditions: 100% DOD, 0.5C charge & discharge at 25°C. System usable energy may vary due to system configuration parameters.

Description of the battery

The VELOCITI-NMC-5139 battery series is the product engineered for E-2W applications. The system integrates an intelligent Battery Management System (BMS) that provides monitoring of cell voltages, current, and temperature. The BMS also performs passive cell balancing to enhance consistency and maximize service life.

www.siegertech.in