



High Performance & Long Life

Delivers over 3500 cycles at 100% Depth of Discharge (DoD), consistent power with low degradation rate

Environment & Safety Focused

IP67 rated- complete protection against dust and solids, protection from thermal runaway.

Robust & Compact Design

Enclosure: CRCA
Connectors: SB75

Smart Connectivity Options

IOT
RS485, CAN, Bluetooth

Battery Management System (BMS)

19S200A smart BMS, IOT feature, real-time protection against overcharge, over-discharge, short circuit, temperature spikes, and thermal runaway.



Technical Data

Model	TEZZ-LFP-60200
-------	----------------

Main Parameter

Battery Chemistry		LFP
Capacity (Ah)		200
Nominal Voltage (V)		60.8
Operating Voltage (V)		47.5-68.4
Nominal Energy (kWh)		12.16
Usable Energy (kWh)		1216
Charge/Discharge Current (A)	Recommended	+60/-100
	Max.	+100/-100
	Peak(25°C)	+100/-100

Other Parameter

Recommend Depth of Discharge	100%
Dimension (L*W*H, mm)	767 x 586 x 324
Weight Approximate(kg)	140
IP Rating of Enclosure	IP67
Operating Temperature	0-55
Recommend Operating Temperature (°C)	Charge: 0-55, Discharge: -10-60
Storage Temperature	At 50% SOC, 25-45°C
Humidity	90% RH
Altitude	<2000 m
Cycle Life	3500 Cycles
Application	E3W
Warranty Period	3 years
Energy delivered over lifetime (kWh)	34048

DC Usable Energy, test conditions: 100% DOD, 0.3C charge & 0.5C discharge at 25°C. System usable energy may vary due to system configuration parameters.

Description of the battery

The Tezz battery series is the product engineered for E-3W applications. The system integrates a Smart Battery Management System (BMS) that provides monitoring of cell voltages, current, and temperature.