



High Performance & Long Life

Delivers over 3500 cycles at 90% Depth of Discharge (DoD), consistent power with low degradation rate

Environment & Safety Focused

Robust & Compact Design

Enclosure: CRCA powder-coated
Connectors: High Voltage Connectors

Smart Connectivity Options

RS485, CAN, Bluetooth

32S60A intelligent BMS, real-time protection against overcharge, over-discharge, short circuit, temperature spikes, and thermal runaway,



Technical Data

Model	LIVIO HV-10250
--------------	-----------------------

Main Parameter

Battery Chemistry		LFP
Built-in Circuit Breaker		Yes
Capacity (Ah)		50
Nominal Voltage (V)		102.4
Operating Voltage (V)		80-116.8
Nominal Energy (kWh)		5.12
Usable Energy (kWh)		4.6
Charge/Discharge Current (A)	Recommend	+25/-50
	Max.	+25/-50
	Peak(25°C)	+30/-50

Other Parameter

Recommended Depth of Discharge	90%
Dimension (L*W*H, mm)	838*395*150
Weight Approximate(kg)	40
IP Rating of Enclosure	IP54
Operating Temperature	0-55
Recommend Operating Temperature (°C)	Charge: 0-55, Discharge: -20-60
Storage Temperature	At 50% SOC, 25-45°C
Humidity	90% RH
Altitude	<2000 m
Cycle Life	3500
Installation	Wall mount
Communication port	RS485, CAN
Warranty Period	5 Years
Energy over lifetime (kWh)	14315

DC Usable Energy, test conditions: 90% DOD, 0.5C charge & discharge at 25°C. System usable energy may vary due to system configuration parameters.

Description of the battery

The LIVIO HV 10250 battery is an advanced energy storage product engineered for stable and reliable power supply across diverse applications. Its design makes it particularly suitable for scenarios requiring high power density, compact installation, reduced structural load, and extended cycle life. The system integrates an intelligent Battery Management System (BMS) that provides real-time monitoring of cell voltage, current, and temperature. The BMS also performs passive cell balancing to enhance consistency and maximize service life.