



Technical Data

Model

LIVIO HV-10230



High Performance & Long Life

Delivers over 2000 cycles at 90% Depth of Discharge (DoD), consistent power with low degradation rate

Environment & Safety Focused

IP54 rated dust protection

Robust & Compact Design

Enclosure: CRCA powder-coated
Connectors: High Voltage Connectors

Smart Connectivity Options

RS485, CAN, Bluetooth

Battery Management System (BMS)

32S60A intelligent BMS, real-time protection against overcharge, over-discharge, short circuit, temperature spikes, and thermal runaway,



Main Parameter		
Battery Chemistry		LFP
Built-in Circuit Breaker		Yes
Capacity (Ah)		50
Nominal Voltage (V)		102.4
Operating Voltage (V)		80-116.8
Nominal Energy (kWh)		3.07
Usable Energy (kWh)		2.76
Charge/Discharge Current (A)	Recommend	+15/-15
	Max.	+30/-30
	Peak(25°C)	+30/-30
Other Parameter		
Recommend Depth of Discharge		90%
Dimension (L*W*H, mm)		
Weight Approximate(kg)		
IP Rating of Enclosure		IP54
Operating Temperature		0-55
Recommend Operating Temperature (°C)		Charge: 0-55, Discharge: -20-60
Storage Temperature		At 50% SOC, 25-45°C
Humidity		90% RH
Altitude		<2000 m
Cycle Life		3500
Installation		Stack
Communication port		RS485, CAN
Warranty Period		5 Years
Energy over lifetime (kWh)		8575

DC Usable Energy, test conditions: 90% DOD, 0.5C charge & discharge at 25°C. System usable energy may vary due to system configuration parameters.

Description of the battery

The LIVIO HV 10230 battery is an advanced energy storage product engineered for stable and reliable power supply across diverse applications. Its design makes it particularly suitable for scenarios requiring high power density, compact installation, reduced structural load, and extended cycle life. The system integrates an intelligent Battery Management System (BMS) that provides real-time monitoring of cell voltage, current, and temperature. The BMS also performs passive cell balancing to enhance consistency and maximize service life.

www.siegertech.in