

Egebant SanSeal 442460

Coating Colour	Blue & Black
Liner Colour	Grey
Liner	Polyester
Coating	Nitrile
Wrist Type	Knit Wrist
Desing	¾ Blue nitrile & ½ Black Sandy nitrile coated, grey liner
Thicknees	1,40 mm
Marking	Transfer Printing



EN ISO 21420

EN 388




4121X

Description

Double-layer 3/4 coated nitrile work glove with high palm grip capability and abrasion resistance for oil/liquid applications.

Dimensions

Egebant SanSeal 442460	Size 7 (S)	Size 8 (M)	Size 9 (L)	Size 10 (XL)	Size 11 (XXL)
Total Glove Length (A) (mm)	240	250	260	270	280
Hand Length (B) (mm)	175	185	195	205	215
Peripheral Length © (mm)	186	192	216	224	228
Over Lock Colour	Red	Black	White	Blue	Burgundy
Glove Weight / 1 Pair (gram)	50	55	59	64	71



a= Total Glove Length
b= Hand Length
c= Peripheral Length

Dimensions and weights can vary by up to 5%

EN Test Results

Test	Notified Body / No	Results / Pass
EN ISO 21420:2020	CTC (0075)	Yes
EN 388: 2016 + A1: 2018	CTC (0075)	4121X

Typical Performance Values

EN ISO 21420:2020 Dexterity	Level 5
EN 388: 2016 + A1: 2018 A. Abrasion Resistance	8000 Cycle
EN 388: 2016 + A1: 2018 A. Blade Cut Resistance	1,4 N
EN 388: 2016 + A1: 2018 A. Tear Resistance	40,68 N
EN 388: 2016 + A1: 2018 A. Puncture Resistance	35,9 N

Speacial Features

REACH Regulation	Meet Requirement
pH Values	Meet Requirement
Azo-colourants and PAHs	Meet Requirement
DMF Free	Yes

Packaging

Pairs Per Poly Bag	12
Poly Bags Per Carton	10
Carton Count	120
Carton Dimensions	S/M/L: 480X260X280 XL/XXL: 480X260X280
Pallet Dimensions	123X80X120

Head Office

A: N:23, TOSB 3. St. Şekerpinar, Çayırova /
Kocaeli 41420 - Turkey
T: +90 262 679 1313 E: info@egebant.com.tr

www.egebant.com.tr