

S250 TRIPLE DECK SCREENER

The McCloskey® S250 Screener rises above all industry standards, positioned as one of the world's largest track mobile screener. The 6' x 22' high-energy 2 bearing 3 deck screenbox delivers more true screening area, and the 225 Hp CAT engine or 218 Hp Volvo engine deliver all the power needed for maximum production.



FEATURES

- ✓ 6' x 22'heavy duty high energy 2 bearing 3 deck screenbox
- ✓ Track mobile
- ✓ 225Hp engine / 218Hp Tier 4 engine
- ✓ Integrated hydraulic folding stockpiling conveyors
- ✓ Remote control tipping grid
- ✓ Fast on-site setup time – 15 minutes typically



The S250 features 900mm (36") wide side conveyors and 800mm (32") wide auxiliary conveyors for higher material flow. All conveyors have individual speed adjustment giving superior material flow control. The Reversible Cross Conveyor removes unwanted chutes which stops blockages and reduces maintenance required. The operator is able to change from a 3-way split to a 4-way split by turning a lever.

The most portable 22' x 6"(6710mm x 1830mm) vibratory screening plant in production. This class leading screening area, along with its high energy screening action, ensure that the McCloskey S250 is the superior choice for aggregate material screening.

S250 TECH SPECS

Engine	168kW (225Hp)
Stockpile Height	
Tail Conveyor	4.99m (16' 4.5")
Side Conveyor	5.40m (17' 8.5")
Screenbox	
Top Deck	6.71m x 1.83m (22' x 6')
Middle Deck	6.71m x 1.83m (22' x 6')
Bottom Deck	6.10m x 1.83m (20' x 6')

TRANSPORT

Height	3.60m (11' 10")
Length	
12' Hopper	18.55m (61' 1.5")
15' Hopper	19.55m (64' 1.5")
Width	3.75m (12' 2")
Weight	42,430kgs (93,541lbs)

OPTIONS

Single or double deck live head | Single shaft shredder | 12' or 15' Hopper

