



The DZH4000TK Series track-mounted horizontal grinder has all the features and mobility of the DZH4000TK and also includes a custom transport system with jeep, providing an economical and efficient way to transport the machine.



SPECIFICATIONS	DZH4000	DZH4000TK	DZH4000TKT
Power	CAT® C18 755 HP Tier 4	CAT® C18 755 HP Tier 4	CAT® C18 755 HP Tier 4
Transmission	Fluid Coupling Drive	Fluid Coupling Drive	Fluid Coupling Drive
Transport dimensions (L x W x H)	42'-1" x 10'-1" x 13'-9" (12.82m x 3.07m x 4.19m)	41'-5" x 10'-7" x 12'-1" (12.62m x 3.22m x 3.68m)	47'-9" x 11'-5" x 13'-8" (14.55m x 3.47m x 4.16m)
Operating dimensions (L x W x H)	61'-0" x 10'-0" x 18'-0" (18.59m x 3.04m x 5.48m)	50'-2" x 10'-4" x 14'-0" (15.3m x 3.16m x 4.26m)	46'-0" x 10'-0" x 14'-0" (14.02m x 3.04m x 4.26m)
Weight	78,500 lbs. (35,380.17 kg)	85,000 lbs. (39,008.91 kg)	100,000 lbs. (45,359.2 kg)
Mill feed opening (W x H)	54.5" x 48" (16.61m x 14.63m)	54.5" x 48" (16.61m x 14.63m)	54.5" x 48" (16.61m x 14.63m)
Screen area	3,800 sq. in. (24,516.08 sq. cm)	3,800 sq. in. (24,516.08 sq. cm)	3,800 sq. in. (24,516.08 sq. cm)
Production	Up to 120 TPH/475 YPH	Up to 120 TPH/475 YPH	Up to 120 TPH/475 YPH

All information subject to change without notice. Please reconfirm any critical details. Production rates based on customer reports, actual throughput will vary depending on on-site specifics.