

SPECTRA BO 35

TECHNICAL DATA SHEET TL 623/2011

Date of issue: 10.8.2011

Date of revision: 3.7.2025

Product characteristics

SPECTRA BO 35 is an aqueous solution of a mixture of potassium soaps with oil and coconut acid soaps.

Use:

SPECTRA BO 35 is used as a liquid separator for batch-off equipment for all types of rubber. Premixes and finished mixes. Base of active ingredients: Soaps and defoamers.

Product features

SPECTRA BO 35 is a yellowish to yellow-brown liquid miscible with water.

| <i>quality</i> | <i>value</i> |
|-------------------------|--------------|
| Dry matter content in % | 29 to32 |
| pH of the sample | 11-12 |

Product processing

The product is suitable for spray and flow-through equipment, as well as for the wading process. The concentration used depends on the rubber formulation and process conditions. The material does not need to be mixed. Protect from frost!

Packaging, storage

SPECTRA BO 35 is supplied in PE drums of capacity 220 litres or in other pre-arranged packaging. It is stored in sealed packages, protected from direct weathering. Recommended storage temperature is +5 to +25°C, hidden from direct sunlight or near heat sources. Protect from frost!

Transport

SPECTRA BO 35 is transported by covered means of transport, not subject to ADR/RID regulations.

Warranty period

If the product is transported and stored according to the above conditions, its warranty period is 12 months from the date of removal.

Note

Data on the properties of the product and its processing were obtained by laboratory measurements and application tests. This data sheet can only provide legally non-binding advice, the product processing must be adapted to the specific conditions.