

RISTIN NEF/BLACK

TECHNICAL DATA SHEET TL 254/2001

Date of issue: 29.5.2001

Date of revision: 4.7.2025

Product characteristics

RISTIN NEF/BLACK is a solution of synthetic resins in a mixture of organic solvents.

Use:

RISTIN NEF is a coating used to protect equipment exposed to aggressive environments of an acidic, alkaline and acidic slightly oxidizing nature. For decorative and aesthetic reasons, the coating can be coloured by adding up to 8 % of aluminium paste without risk of deterioration of mechanical properties – **RISTIN NEF-AL**. Black colouring may also be added – **RISTIN NEF/BLACK**.

Product features

RISTIN NEF/BLACK is a dark brown/black low viscosity liquid with an ester odour.

<i>quality</i>	<i>value</i>
Dry matter content in %	min. 40

Product processing

The product serves as a fast-drying coating for both absorbent and non-absorbent (metal) surfaces. It produces hard films with lower elasticity, adhering well to a wide variety of substrates.

Packaging, storage

RISTIN NEF/BLACK is supplied in galvanized drums of capacity 200 litres or in other pre-arranged packaging. It is stored in sealed packages, protected from direct weathering. Recommended storage temperature is +5 to +25°C, hidden from direct sunlight or near heat sources. Storage at temperatures below 0 °C does not adversely affect its application properties.

Transport

RISTIN NEF/BLACK is transported by covered means of transport in accordance with ADR/RID regulations.

Warranty period

If the product is transported and stored according to the above conditions, its warranty period is 12 months from the date of removal.

Note

Data on the properties of the product and its processing were obtained by laboratory measurements and application tests. This data sheet can only provide legally non-binding advice, the product processing must be adapted to the specific conditions.