

PEDISOL PD 3X

TECHNICAL DATA SHEET TL 844/2019

Date of issue: 26.4.2019

Date of revision: 3.7.2025

Product characteristics

PEDISOL PD 3X is an aqueous dispersion of paraffinic hydrocarbons.

Use:

PEDISOL PD 3X is used as a filler and hydrophobizing agent for industrial purposes.

Product features

PEDISOL PD 3X is a yellowish to brownish liquid paste of anionic character. Its density may increase during storage. It is dilutable with water in any proportion. It is resistant to hard water and is stable in slightly acidic, neutral and slightly alkaline environments.

PEDISOL PD 3X must comply with these features:

<i>quality</i>	<i>value</i>
Dry matter content in %	min. 35
pH of the sample	6-8

Product processing

It is recommended to mix the product into a smooth paste before processing. It can then be diluted with any amount of cold water. Solutions must not be boiled.

Packaging, storage

PEDISOL PD 3X is supplied in PE cans of capacity 50 litres or in other pre-arranged packaging. It is stored in sealed packages, protected from direct weathering. Recommended storage temperature is +5 to +30°C, hidden from direct sunlight or near heat sources. Protect from frost!

Transport

PEDISOL PD 3X is transported by covered means of transport, not subject to ADR/RID regulations. During transport protect from frost!

Warranty period

If the product is transported and stored according to the above conditions, its warranty period is 12 months from the date of removal. The shelf life is 12 months from the date of manufacture.

Note

Data on the properties of the product and its processing were obtained by laboratory measurements and application tests. This data sheet can only provide legally non-binding advice, the product processing must be adapted to the specific conditions.