

RETOSTAN B

TECHNICAL DATA SHEET TL 248/2001

Date of issue: 11.6.2003

Date of revision: 3.7.2025

Product characteristics

RETOSTAN B is an aqueous solution of the condensation product of epichlorohydrin and polyaminoamide of organic acids.

Use:

RETOSTAN B is a flocculating and retention agent used in the paper industry and wastewater treatment plants.

Product features

RETOSTAN B is a yellow to yellow-brown liquid, moderate viscosity and of kationic character. **RETOSTAN B** solutions are prepared by mixing the product with cold or lukewarm water. Solutions must not be boiled.

RETOSTAN B must comply with these features:

<i>Quality sign</i>	<i>Value</i>
Viscosity while 20 °C in mPa.s	250-700
Dry matter content in %	min. 27

Product processing

The product is widely used in the paper industry and for wastewater treatment in various areas of the economy.

Packaging, storage

RETOSTAN B is supplied in PE cans of capacity 50 litres or in other pre-arranged packaging. Its transport in tankers is also suitable. It is stored in sealed packages, protected from direct weathering. Recommended storage temperature is +5 to +25°C, hidden from direct sunlight or near heat sources.

Transport

RETOSTAN B is transported by covered means of transport, not a subject to ADR/RID regulations.

Warranty period

If the product is transported and stored according to the above conditions, its warranty period is 12 months from the date of removal.

Note

Data on the properties of the product and its processing were obtained by laboratory measurements and application tests. This data sheet can only provide legally non-binding advice, the product processing must be adapted to the specific conditions.