

DEFOAMER E

TECHNICAL DATA SHEET

Date of issue: 20.1.2023

Date of revision: 4.7.2025

Product characteristics

Silicone Defoamer E is an aqueous emulsion of an active silicone component, further diluted with water.

Use:

It is designed to control unwanted foaming of a number of industrial processes and in wastewater treatment plants, even under harsh temperature and chemical conditions.

Product features

The defoaming effect is very fast, almost instantaneous. The dosage is low and does not affect production capacity. They are easily dispersed in water to dilute application solutions.

Defoamer E is an white aqueous silicone emulsion.

<i>quality</i>	<i>value</i>
Dry matter content in %	min. 20
pH of solution	3 - 6
Density (kg/m ³)	980 - 1020
Viscosity (mPa/20°C)	5 - 30

Product processing

The E skimmer is designed to control undesirable foaming of water systems in various technological processes and waste management. It is mainly used in: chemical processes, processing of oils, bitumen and tars. Production of bitumen emulsions, washing of gases, impregnation processes. Paper, textile and leather industries. Wastewater treatment, washing and degreasing processes

Packaging, storage

RETAPON DN is supplied in tin barrels of capacity 200 litres or in other pre-arranged packaging. It is stored in sealed packages, protected from direct weathering. Recommended storage temperature is +5 to +30°C, hidden from direct sunlight or near heat sources. Storage at temperatures below 0 °C does not adversely affect the application properties of the product.