

FILLER FF

TECHNICAL DATA SHEET TL 497/2009

Date of issue: 22.9.2008

Date of revision: 4.7.2025

Product characteristics

FILLER FF is a powdery substance. It is a mixture of mineral powders and an acid-reactive catalyst.

Use:

FILLER FF is the powder component of **EBOLIT FF** sealant. It is used for the construction of chemically resistant linings and floors as a base and jointing compound.

Product features

FILLER FF resists dilute inorganic acids, salt solutions, gasoline, oil, diesel. It does not resist alkalis, e.g. sodium hydroxide, or solvents such as acetone and pyridine.

Packaging, storage

FILLER FF is supplied in PE bags of 25 or 50 kg, in plastic buckets with lids of 5 or 10 kg or in other pre-arranged packaging. It is stored in sealed packages, protected from direct weathering. Recommended storage temperature is +5 to +30°C, hidden from direct sunlight or near heat sources.

Transport

FILLER FF is transported by covered means of transport, not subject to ADR/RID regulations.

Warranty period

If the product is transported and stored according to the above conditions, its warranty period is 12 months from the date of removal.

Note

Data on the properties of the product and its processing were obtained by laboratory measurements and application tests. This data sheet can only provide legally non-binding advice, the product processing must be adapted to the specific conditions.