

ISOPAL P 150

TECHNICAL DATA SHEET

Date of issue: 20.5.2021

Date of revision: 2.7.2025

Product characteristics

ISOPAL P 150 is a polyamide derivate

Use:

ISOPAL P 150 is an egalising agent fro dyeing cullulose and bast fibres with cyp and direct dyes.

Product features

ISOPAL P 150 is an amber-yellow clear liquid of non-ionic character. It is infinitely miscible with water. It is an egalising agent specially designed for dyeing cotton, flax and cellulose fibres and offers a wide range of applications due to its high stability in different application conditions due to its moderate foaming effect.

ISOPAL P 150 must comly with these features:

| Quality sign | Value |
|------------------------------------|-------|
| pH of the solution g/litre | 7-9 |
| Density 20 °C in kg/m ³ | 1020 |

Product processing

The product is used for dyeing collulotic and bast textile fabrics

Packaging, storage

ISOPAL P 150 is supplied in PE drums of 200 litres or in other pre-arranged packaging. It is stored in sealed packages, protected from direct weathering. Recomendated storage temperature is +5 to +25°C, hidden from direct sunlight or near heat sources.

Transport

ISOPAL P 150 is transported by covered means of transport, not a subject to ADR/RID regulations.

Warranty period

If the product is transported and stored according to the above conditions, its warranty period is 12 months from the date of removal.

Note

Data on the properties of the product and its processing were obtained by laboratory measurements and application tests. This data sheet can only provide legally non-binding advice, the product processing must be adapted to the specific conditions.