

KORYNT 30 CN

TECHNICAL DATA SHEET TL 286/2002

Date of issue: 16.9.2002

Date of revision: 27.6.2025

Product characteristics

Synergistic blend of surfactants and glycol.

Use:

Industrial non-foaming degreasing agent. It is used in a diluted state for degreasing and washing all metal and non-metal surfaces contaminated with oils with mechanical impurities.

Product features

KORYNT 30 CN is a moderately viscous, colourless to slightly yellowish liquid. It is miscible with water in every ratio.

KORYNT 3160 must meet the following quality characteristics:

Quality sign	Value
Dry matter in %	14,8 – 15,8
pH of 1% solution	5 - 7

Product processing

KORYNT 30 CN is well miscible with cold water. Recommended concentration of the product in the degreasing bath is 1 to 3%, the working temperature of the bath is from about 30 °C. If it is used for degreasing products where it is necessary to ensure short-term protection of the surface against corrosion, the **KORYNT 3160** passivating agent is added to the degreasing bath at a concentration of 0.5 to 1.5%.

Packaging, storage

KORYNT 3160 is supplied in PE cans with a volume of 50 liters or in other pre-agreed packaging. It is stored in sealed containers in places protected from direct weather conditions. The recommended storage temperature is +5 to +25 °C.

Transport

KORYNT 30 CN is transported by covered vehicles. It is not subject to ADR/RID regulations.

Warranty period

If the product is transported and stored according to the above conditions, its warranty period is 12 months from the date of removal.

Note

Data on the properties of the product and its processing were obtained by laboratory measurements and application tests. However, this data sheet can only provide legally non-binding advice, the product processing must be adapted to the specific conditions.