

EBOLIT FF

TECHNICAL DATA SHEET TL 151/2001

Date of issue: 13.3.2003

Date of revision: 4.7.2025

Product characteristics

EBOLIT FF is a modified phenol-furaldehyde resin suitable for the preparation of chemically resistant linings and floors exposed to oxidizing acids.

Use:

Resin **EBOLIT FF** is processed in combination with powdered **FILLER AB** into a self-hardening sealant. It is used as a binder of ceramic tiles and fittings for the purpose of chemically resistant protection of buildings and technological ensembles.

Product features

EBOLIT FF is a brown-black liquid of characteristic odour.

<i>quality</i>	<i>value</i>
Consistency at 20 °C in s	70 to 150
pH of the aqueous leach	6,5-7,5

Product processing

The product can be used as a lining putty, as a binder of ceramic tiles and fittings for the purpose of chemically resistant protection of buildings and technological ensembles.

Packaging, storage

EBOLIT FF is supplied in metal drums of capacity 200 litres or in other pre-arranged packaging. It is stored in sealed packages, protected from direct weathering. Recommended storage temperature is +5 to +30°C, hidden from direct sunlight or near heat sources. Storage at temperatures below 0 °C does not adversely affect its application properties.

Transport

EBOLIT FF is transported by covered means of transport, not subject to ADR/RID regulations.

Warranty period

If the product is transported and stored according to the above conditions, its warranty period is 12 months from the date of removal.

Note

Data on the properties of the product and its processing were obtained by laboratory measurements and application tests. This data sheet can only provide legally non-binding advice, the product processing must be adapted to the specific conditions.