

EBOLIT 508/XXXX

TECHNICAL DATA SHEET TL 498/2009

Date of issue: 12.1.2009

Date of revision: 4.7.2025

Product characteristics

EBOLIT 508/XXXX is a low molecular weight epoxy resin modified with reactive diluents containing pigments and fillers.

Use:

EBOLIT 508/XXXX is a self-levelling flooring material for the preparation of seamless floors in interiors. It is cured with a suitable hardener before application.

Product features

EBOLIT 508/XXXX is a muddy viscous liquid with RAL shade.

<i>quality</i>	<i>value</i>
Consistency of the spout cup 6 mm at 23 °C, in s	50 to 120
Shade according to RAL scale	According to customer requirements

Product processing

The product is applied to dry, flat, crack-free, mature concrete insulated against the effects of underground moisture, free of dust and loose particles, stains from oils, asphalt, paints, diesel or other substances reducing adhesion.

Packaging, storage

EBOLIT 508/XXXX is supplied in metal drums of capacity 200 litres or in other pre-arranged packaging. It is stored in sealed packages, protected from direct weathering. Recommended storage temperature is +5 to +30°C, hidden from direct sunlight or near heat sources. Storage at temperatures below 0 °C does not adversely affect its application properties.

Transport

EBOLIT 508/XXXX is transported by covered means of transport in accordance with ADR/RID regulations.

Warranty period

If the product is transported and stored according to the above conditions, its warranty period is 12 months from the date of removal.

Note

Data on the properties of the product and its processing were obtained by laboratory measurements and application tests. This data sheet can only provide legally non-binding advice, the product processing must be adapted to the specific conditions.