

BENT OP

TECHNICAL DATA SHEET TL 289/2002

Date of issue: 11.10.2002

Date of revision: 30.6.2025

Product characteristics

An aqueous alcohol solution of a mixture of anionic and nonionic surfactants and excipients.

Use:

In a concentrated state, it is used to wash heavily oiled greasy machines, engines, objects, etc. In a diluted state, when applying 1 to 2 tablespoons per 5 liters of water, it is used to wash all types of floor coverings, window frames, removing flies from car windows, etc.

Easily removes stubborn or greasy dirt.

BENT OP is suitable for machine washing of floor coverings!

Product features

Low-viscosity liquid of light pastel color with a delicate fresh fragrance.

Packaging, storage

BENT OP is supplied in PE cans with a capacity of 25 litres or in other pre-agreed packaging. It is stored in sealed containers in places protected from direct weather conditions. The recommended storage temperature is +5 to +25 °C. Short-term exposure to colder temperatures, for example during transport, does not affect the application properties of the product.

Transport

EBOL KCO II is transported by covered means of transport and is not subject to ADR/RID regulations.

Warranty period

If the product is transported and stored according to the above conditions, its warranty period is 12 months from the date of removal.

Note

Data on the properties of the product and its processing were obtained by laboratory measurements and application tests. However, this data sheet can only provide legally non-binding advice, the product processing must be adapted to the specific conditions.