

# EBOL KCO

## TECHNICAL DATA SHEET TL 415/2006

Date of issue: 7.8.2006

Date of revision: 30.6.2025

### Product characteristics

**EBOL KCO** is an aqueous solution of a mixture of surfactants, organic solvents and inorganic hydroxide.

### Use:

**EBOL KCO** is a highly effective cleaning product. Thanks to its composition, it disrupts the structure of impurities and sludge and ensures that they are washed away.

**EBOL KCO** is used for cleaning non-absorbent surfaces.

It can be recommended for floors, machinery and equipment in car repair shops, truck garages, hangars, meat packing plants, printers, industrial plants, workshops, etc.

### Product features

**EBOL KCO** is a yellow liquid, infinitely miscible with water, non-flammable.

Quality sign	Value
Dry matter in %	Min. 5
pH of 1% solution	11,5 - 13

### Product processing

The product is applied by spraying, sprinkling or spreading on the cleaned surface. It is left on for 30 to 60 seconds and the surface is rinsed with water. We recommend wiping dry. If necessary, the procedure can be repeated several times.

**EBOL KCO** attacks aluminum and its alloys! When used on these metals, it is necessary to dilute as much as possible with water and reduce the exposure time to a minimum. We recommend testing the product on a small area in a hidden place first.

### Packaging, storage

**EBOL DKB** is supplied in PE cans with a capacity of 50 litres or in other pre-agreed packaging. It is stored in sealed containers in places protected from direct weather conditions. The recommended storage temperature is +5 to +25 °C. Short-term exposure to colder temperatures, for example during transport, does not affect the application properties of the product.

### Transport

**EBOL KCO** is transported by covered vehicles in accordance with ADR/RID regulations.

### Warranty period

---

If the product is transported and stored according to the above conditions, its warranty period is 12 months from the date of removal.

**Note**

Data on the properties of the product and its processing were obtained by laboratory measurements and application tests. However, this data sheet can only provide legally non-binding advice, the product processing must be adapted to the specific conditions.