Drill smarter, work safer and finish faster with SNAPDRILL



Self-centering clamping mechanism
→ Reduces the risk of injuries and guarantees precise drilling.

Automatic feed
→ No manual pushing required – less fatigue.

Lightweight, handheld design
→ Flexible and mobile, even overhead or in tight spaces.

Durable hole saws
→ 400 holes per saw – significantly lower tool costs.

Improve margins with on-site fabrication
→ Avoid costly rework, slow threading and expensive prefab - save up 50% of the cost

www.snapdrill.no SNAPDRILL

SNAPDRILL

For more than 5 years, we have helped contractors all over the world install smarter and safer. Snapdrill revolutionizes the on-site fab process, making it cheaper and more flexible than ever. One fitter with a Snapdrill, can fab faster than you can hang the prefab pipe. The unique specs makes it easy, precise and safe to use wherever you need to drill holes. Read below how Snapdrill wins.

Visit www.snapdrill.no/roi to calculate your return on investment.

Case studies

"Snapdrill has been received very well with all the engineers. Our fabrication shop reckons it's now at least 50% quicker drilling out the holes for the welder rather than our traditional method of using the plasma cutter."
Jamie Boyle - Head of UK Sprinklers, Glasgow

WSFP Colorado Springs paid off their Snapdrill on the first job. The crew finished early, came in under budget, and avoided costly rework thanks to to combination of user-friendliness, precision and speed of Snapdrill.

After discovering Snapdrill, Fire NZ on southern island on New Zealand completely changed their installation method: they now hang all pipe first and drill everything in place. The switch from threaded tees to Mechanical Ts cut installation time from 10 minutes to 2 — tripling daily output and transforming workflows across all types of work.

The biggest mechanical contractor in Sweden, Bravida, report that Snapdrill delivers faster, safer and more ergonomic installation — "even the sceptical old-timers love it". Fitters report cleaner, perfectly centered holes and far less strain, making Mechanical Ts quicker and more reliable than ever.

Compressor manufacturer in Pennsylvania, FS Elliott, report that Snapdrill delivered full ROI in weeks. By eliminating the need to haul pipe to a drill press and allowing holes to be drilled directly in place, FS-Elliott saved hours of production time per week, reduced tool wear, and streamlined their entire fabrication flow.

Complete Standard kit

- Best value option
- Snapdrill pipe hole cutting machines for 1-1/4, 1-1/2, 2, 2-1/2 and 4 inch pipe
- Required power unit
- High-speed charger (30m full charge) and two batteries for all day productivity
- Robust IP67 rated case with wheels for easy and safe on-site transportation
- Two of each of our long life hole saws for 24, 30, 38,1, 44,5, 50,8, 63,5 and 70mm

3 and 6-inch kit

- Snapdrill pipe hole cutting machines for 3 and 6 inch pipe
- Room for power unit setup (not included)
- Robust IP67 rated case with wheels for easy and safe on-site transportation
- Hole saws sold separately

Custom kit

- Choose your sizes of machines and hole saws





Build your kit

1. Choose your Snapdrill machines / pipe sizes

We have machines for pipes with diameters of 1-1/4+1-1/2 (combination), 2, 2-1/2, 3, 4 and 6 inches.

They are manufactured per pipe size to ensure ease of use. It enables a true hand-held format, only 2,5kg per unit.



2. Choose your hole saws



For Mechanical Ts

Ø24Lmm hole saw for SD60.3 and larger (15/16" hole saw for 2" Snapdrill and larger)
Ø24Smm hole saw only for SD42.4/48.3 (15/16" hole saw, only for 1-1/4 + 1-1/2 inch)
Ø30Lmm hole saw for SD60.3 and larger (1-3/16" hole saw for 2" Snapdrill and larger)
Ø30Smm hole saw only for SD42.4/48.3 (1-3/16 hole saw only for 1-1/4 + 1-1/2 Snapdrill)
Ø38.1 mm hole saw (1-1/2")
Ø44.5 mm hole saw (1-3/4")
Ø46mm hole saw(1-13/16")
Ø50.8 mm hole saw (2")
Ø54mm hole saw (2-1/8")
Ø63.5 mm Hole Saw (2-1/2")
Ø70mm hole saw (2-3/4")

For welding

17mm hole saw - only for SD42
Ø21mm hole saw (13/16") for SD60 and higher
Ø21mm hole saw (13/16") only for SD42
Ø27mm hole saw (1-1/16") for SD60 and higher
Ø27mm hole saw (1-1/16") for SD42 only
Ø33.7 mm hole saw (1-5/16") for SD60 and higher
Hole saw Ø33.7 mm (1-5/16") only for SD42
Ø42.4 mm (1-11/16") Hole saw
Ø48.3 mm (1-23/32") hole saw
Ø60.3 mm (2-3/8") hole saw