

# Declaration of Performance

**DOP 251112-13361-13362**

**1. Product Type:**

Unique identification code of the product –type:

**BossCover Pond EPDM**

**2. Type:**

Batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

**EPDM Waterproofing membrane  
(lining) 1.00 mm, 1.14 mm, 1.20 mm, 1.52 mm**

**3. Intended use:**

Or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer:

**Non reinforced, black, rubber membrane made of Ethylen-Propylen-Dien-Terpolymer (EPDM) according to EN 13361 & EN 13362, used as a waterproofing membrane in the construction of reservoirs, dams and canals.**

**4. Name, registered Trade name:**

Or registered trade mark and contact address of the manufacture as required under Article 22(5):

**BossCover Nederland  
De Poort 21, 4411 PB Rilland  
Nederland**

**5. Contact Address:**

Where applicable, am and contact address of the authorized representative whose mandate covers the tasks specified in Article 12(2):

**Not applicable**

**6. AVCP:**

System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:

**System 2+**

**7. Notified body:**

In case of the declaration of performance concerning a construction product covered by a harmonized standard:

**Notified certification body No. 1922 performed the initial inspection of the manufacturing plant and factory production control and issued the certificate of conformity of the production control: 1922-CPR-2485.**

**8. Notified Body:**

In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

**Not relevant (see 7).**

## 9. Declared performance:

Essential Characteristics	Unit	Test Standard	Value or statement
Visible defects	-	EN 1850-2	Pass
Length	mtr	EN 1848-2	-0%, +5%
Width	mtr	EN 1848-2	-0.5%, +1%
Thickness	mm	EN 1849-2	-5%, +10%
Mass per unit area	kg/m <sup>2</sup>	EN 1848-2	-5%, +10%
Tensile strength	N/mm <sup>2</sup>	EN 12311-2	≥ 8.0
Elongation	%	EN 12311-2	≥ 300
Tear resistance	N	ISO 34-1	≥ 20.0
Resistance to static puncture	kN	EN 12236	≥ 0.50
Water permeability	m <sup>3</sup> /m <sup>2</sup> d	EN 14150	4.0 ± 10 <sup>-6</sup>
Low Temperature behavior	°C	EN 495-5	≤ -45
Weathering (3000 hrs)	--	EN 12224	Pass
Oxidation	--	EN 14575	Pass

## 10. Declaration:

The performance of the product identified in point 1 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4. Signed for and on behalf of the distributor by:

**John van der Reest**  
**BossCover Nederland / BossCover België**  
**Rilland, november 2025**

1922-CPR-2485