

Declaration of Performance

DoP 250901-13984

In accordance with Regulation (EU) No. 305/2011 (CPR)

1. Product type

BossCover VapourShield HM

2. Identification of the construction product

Production code: see product and/or packaging

3. Intended use

Self-adhesive vapour control layer in accordance with EN 13984:2013, Type A, intended for use as a vapour barrier in warm roof constructions.

4. Manufacturer

BossCover Nederland
De Poort 21
4411 PB Rilland
The Netherlands

5. Authorised representative

Not applicable

6. System of assessment and verification of constancy of performance (AVCP)

System 3

7. Notified body(ies)

Kiwa BDA Testing, notified body No. 1640, performed the determination of the product type on the basis of type testing for the relevant characteristics in accordance with EN 13984:2013.

8. European Technical Assessment (ETA)

Not applicable

9. Declared performance

Essential Characteristics	Unit	Test standard	Performance
Water tightness	-	EN-1928	Pass
Resistance to tearing (nail shank), longitudinal	N	EN-12310-1	≥ 350
Resistance to tearing (nail shank), transverse	N	EN-12310-1	≥ 380
Tensile strength, longitudinal	N/50 mm	EN-12311-2	≥ 850
Tensile strength, transverse	N/50 mm	EN-12311-2	≥ 850
Elongation at break, longitudinal	%	EN-12311-2	≥ 2,5
Elongation at break, transverse	%	EN-12311-2	≥ 3,0
Shear resistance of joints, longitudinal	N/50 mm	EN-12317-2	≥ 700
Shear resistance of joints, transverse	N/50 mm	EN-12317-2	≥ 450
Water vapour transmission (Sd-value)	m	EN-1931	≥ 1500
Reaction to fire	Class	EN-13501-1	F

10. Declaration

The performance of the product identified in point 1 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

John van der Reest
Sr. Technical Specialist Certification & Quality Control

Rilland, April 2026