

Maintenance Manual for Betonepox[®] Polished Plaster

PROCEDURE

Wipe the surface with a damp, clean cloth soaked in clean water. For heavier soiling, mild detergents such as Dawn Soap or similar household cleaning agents may be used. If necessary, a disinfectant such as bleach can also be applied. Under no circumstances should cleaning products containing fine abrasives or sand be used, as they could damage the final layer of the varnish, fine filler, or lacquer.

Please also ensure that no adhesive tapes are applied to the surface, except for STORCH purple masking tape 30 mm x 50 m – paper special (96093022), which must be carefully removed after each use. Rough removal could again cause damage to the final layer of the varnish, fine filler, or lacquer.

NOTICE

In the case of polished plaster applied on floors, behind kitchen units, in bathrooms, or inside shower enclosures, it is necessary to regularly check the condition of sealants in the corners of the surface finish. If the sealant is cracked or damaged, please contact our company as soon as possible.

RECOMMENDATION

When using the polished plaster as flooring, consider the use of office chairs with wheels. The most important factor is choosing the correct type of castors suitable for our surface finish. Based on our experience, we recommend GROVENTI – Conffice wheels.

For all surfaces, if heavy soiling or damage occurs, please contact our company at dokumenty@nemec.eu. We will be happy to recommend the right solution for your specific issue.

