



Disposable Steel Cylinder

- Material:** · Mild Steel Q235B / Q335B / DC04
- Specification:** · ISO 11118 compliant, TPED Pi certified
· DOT 39 compliant & certified
- Volume:** · 0.3L- 6.7L
- Valve Outlet:** · M10x1, M11x1, M12x1
- Finish:** · powder coated (standard finish)
- Graphic:** · shrink sleeve / label (optional)
- Accessories:** · plastic base / nozzle (optional)

ISO 11118 Series (110/120/150bar)

Water Volume (l)	Work Pressure (bar)	Test Pressure (bar)	CO ₂ Capacity (g)	Diameter (mm)	Length (mm)	Weight (kg)	Material
0.95	110	165	600	70	305	1.43	Q235B
1.0	110	165	630	70	324	1.49	Q235B
1.1	110	165	700	70	351	1.62	Q235B
1.2	110	165	750	100	200	1.47	Q355B
1.8	110	165	1100	100	284	1.97	Q355B
2.0	110	165	1200	100	313	2.14	Q355B
2.2	110	165	1400	100	341	2.31	Q355B
3.3	110	165	2000	118	365	3.48	Q355B

Custom dimensions / specifications available upon request

DOT 39 Series (1600psi)

Water Volume (l)	Work Pressure (psi)	Test Pressure (psi)	CO ₂ Capacity (g)	Diameter (mm)	Length (mm)	Weight (kg)	Material
0.95	1600	2000	640	80	235	1.10	DC04

Custom dimensions / specifications available upon request