



# FIRE EXTINGUISHERS

2026 EDITION

# CATALOGUE

<b>ABC Powder Fire Extinguishers</b> .....	<b>01</b>
-Stored Pressure ABC Powder Fire Extinguishers .....	01
-Cartridge Operated ABC Powder Fire Extinguishers.....	02
<b>Fluorine Free Foam Fire Extinguisher</b> .....	<b>03</b>
-Stored Pressure FF Foam Fire Extinguishers .....	03
-Cartridge Operated FF Foam Fire Extinguishers.....	04
<b>Water Additive Fire Extinguisher</b> .....	<b>05</b>
-Stored Pressure Water Additive Fire Extinguishers .....	05
-Cartridge Operated Water Additive Fire Extinguishers.....	06
<b>Wet Chemical Fire Extinguisher</b> .....	<b>07</b>
-Stored Pressure Wet Chemical Fire Extinguishers .....	07
<b>CO2 Fire Extinguisher</b> .....	<b>08</b>
-Stored Pressure CO2 Steel Fire Extinguishers .....	08
-Stored Pressure CO2 Aluminium Fire Extinguishers.....	09
<b>Wheeled Mobile Trolley ABC Powder Fire Extinguishers</b> .....	<b>10</b>
-Stored Pressure ABC Powder Wheeled Mobile Fire Extinguishers .....	10
-Cartridge Operated ABC Powder Wheeled Mobile Fire Extinguishers.....	11

## ABC POWDER FIRE EXTINGUISHER

### Stored Pressure

- Suitable for class A B C fires
- Forged Anodized aluminum valve (6-12kg)
- Forged brass valve (2kg)
- CE approved phosphated steel cylinder with polyester powder coating
- High performance dry chemical powder according to DIN EN 615
- 100% helium leak detected.
- Pressure release valve included (except PD2-A)
- Production under ISO 9001 quality system
- CE, DIN EN 3, MED, GS Mark
- 2kg models complete with wire bracket
- 5 year warranty



Model Number	PD2-A	PD6E-E	PD9E-E	PD12E-E
Capacity (kg)	2	6	9	12
Cylinder Diameter (mm)	110	150	182	190
Fire Rating	13A/89B/C	34A/233B/C	43A/233B/C	55A/233B/C
Extinguisher Weight (kg)	3.70	9.60	14.20	17.90
Range of Throw (m)	>2	>4	>4	>8
Duration of Discharge (secs)	11	19	21	27
Working Pressure (bar) at 20°C	14	14	14	14
Test Pressure (bar)	30	30	30	30
Operation Temperature (°C)	-30 to +60	-30 to +60	-30 to +60	-30 to +60
GS Mark	✓	✓	✓	✓
MED Approved	✓	✓	✓	✓
DIN EN 3 Approved	✓	✓	✓	✓
Packing Size (LxWxH) (mm)	425x125x130	565x240x160	595x265x195	660x285x205



## ABC POWDER FIRE EXTINGUISHER

### Gas Cartridge Operated

- Suitable for class A B C fires
- Forged anodized aluminium valve
- CE approved phosphated steel cylinder with polyester powder coating
- TPED approved Gas Cartridge
- High performance dry chemical powder according to DIN EN 615
- Pressure release valve included
- Production under ISO 9001 quality system
- CE, DIN EN 3, MED, GS Mark
- 5 year warranty



Model Number	GPD6	GPD6E-E	GPD9	GPD12E
Capacity (kg)	6	6	9	12
Cylinder Diameter (mm)	150	150	182	182
CO2 Gas Cartridge (g)	150	150	200	225
Fire Rating	55A/233B/C	34A/233B/C	55A/233B/C	55A/233B/C
Extinguisher Net Weight (kg)	10.60	10.60	15.20	18.70
Range of Throw (m)	>4	>4	>4	>4
Duration of Discharge (secs)	15	17	21	28
Test Pressure (bar)	30	30	30	30
Operation Temperature (°C)	-30 to +60	-30 to +60	-30 to +60	-30 to +60
GS Mark	✓	✓	✓	✓
MED Approved	✓	✓	✓	✓
DIN EN 3 Approved	✓	✓	✓	✓
Packing Size (LxWxH) (mm)	565x255x175	566x255x175	580x260x190	620x280x200



## FLUORINE FREE FOAM EXTINGUISHERS

### Stored Pressure

- Suitable for class A B fires
- Forged nickel plated brass valve and collar
- CE approved internally lined phosphated steel cylinder with polyester powder coating
- 100% leak detected
- Tested to 35kV
- Pressure release valve included
- Production under ISO 9001 quality system
- CE, DIN EN 3, MED, GS Mark
- 2L model complete with wire bracket
- 5 year warranty



Model Number	FM2-FF	FM6-FF	FM9-FF
Capacity (L)	2	6	9
Cylinder Diameter (mm)	110	162	182
Fire Rating	5A/34B	21A/144B	27A/233B
Extinguisher Weight (kg)	4.00	10.30	14.50
Range of Throw (m)	>2	>4	>4
Duration of Discharge (secs)	17	39	67
Working Pressure (bar) at 20°C	14	14	14
Test Pressure (bar)	30	30	30
Operation Temperature (°C)	+5 to +60	+5 to +60	+5 to +60
GS Mark	✓	✓	✓
MED Approved	✓	✓	✓
DIN EN 3 Approved	✓	✓	✓
Packing Size (LxWxH) (mm)	445x140x125	605x200x175	660x260x192



## FLUORINE-FREE FOAM FIRE EXTINGUISHERS

### Gas Cartridge Operated

- Suitable for class A B fires
- Forged anodized aluminum valve
- CE approved internally lined phosphated steel cylinder with polyester powder coating
- TPED approved Gas Cartridge
- Tested to 35kV
- Pressure release valve included
- Production under ISO 9001 quality system
- CE, DIN EN 3, MED, GS Mark
- 5 year warranty

Model Number	GFM6-FFA	GFM9-FFA
Capacity (L)	6	9
Cylinder Diameter (mm)	162	182
CO2 Gas Cartridge (g)	55	75
Fire Rating	27A/144B	34A/183B
Extinguisher Weight (kg)	10.40	14.70
Range of Throw (m)	>4	>4
Duration of Discharge (secs)	54	84
Test Pressure (bar)	30	30
Operation Temperature (°C)	+5 to +60	+5 to +60
GS Mark	✓	✓
MED Approved	✓	✓
DIN EN 3 Approved	✓	✓
Packing Size (LxWxH) (mm)	570x280x175	620x285x200



## WATER ADDITIVE FIRE EXTINGUISHER

### Stored Pressure

- Suitable for class A fire with high performance rating
- Forged nickel plated brass valve and collar
- CE approved internally lined phosphated steel cylinder with polyester powder coating
- 100% leak detected
- Tested to 35kV
- Pressure release valve included
- Production under ISO 9001 quality system
- CE, DIN EN 3, MED, GS Mark
- 5 year warranty

Model Number	WT6-A
Capacity (L)	6
Cylinder Diameter (mm)	162
Fire Rating	43A
Extinguisher Weight (kg)	10.90
Range of Throw (m)	>4
Duration of Discharge (secs)	43
Working Pressure (bar) at 20°C	14
Test Pressure (bar)	30
Operation Temperature (°C)	+5 to +60
GS Mark	✓
MED Approved	✓
DIN EN 3 Approved	✓
Packing Size (LxWxH) (mm)	610x255x175



## WATER ADDITIVE FIRE EXTINGUISHER

### Gas Cartridge Operated

- Suitable for class A fire with high performance rating
- Forged nickel plated brass valve
- CE approved internally lined phosphated steel cylinder with polyester powder coating
- TPED approved Gas Cartridge
- Tested to 35kV
- Pressure release valve included
- Production under ISO 9001 quality system
- CE, DIN EN 3, MED, GS Mark
- 5 year warranty

Model Number	GWT6-A
Capacity (L)	6
Cylinder Diameter (mm)	162
CO2 Gas Cartridge (g)	55
Fire Rating	43A
Extinguisher Weight (kg)	11.40
Range of Throw (m)	>4
Duration of Discharge (secs)	44
Test Pressure (bar)	30
Operation Temperature (°C)	+5 to +60
GS Mark	✓
MED Approved	✓
DIN EN 3 Approved	✓
Packing Size (LxWxH) (mm)	560x280x180



## WET CHEMICAL FIRE EXTINGUISHER

### Stored Pressure

- Suitable for A F type of fires
- Wet chemical process seals the surface of burning oil to prevent re-ignition
- Forged nickel plated brass valve and collar
- CE approved internally lined phosphated steel cylinder with polyester powder coating
- 100% leak detected
- Tested to 35kV
- Pressure release valve included
- Production under ISO 9001 quality system
- CE, DIN EN 3, MED, GS Mark
- 5 year warranty

Model Number	WC6
Capacity (L)	6
Cylinder Diameter (mm)	162
Fire Rating	13A/75F
Extinguisher Weight (kg)	11.30
Range of Throw (m)	>2
Duration of Discharge (secs)	42
Working Pressure (bar) at 20°C	14
Test Pressure (bar)	30
Operation Temperature (°C)	+5 to +60
GS Mark	✓
MED Approved	✓
DIN EN 3 Approved	✓
Packing Size (LxWxH) (mm)	685x220x175



## STEEL CO2 FIRE EXTINGUISHER

### Stored Pressure

- Suitable for class B fires
- CE approved brass valve
- CE approved high tensile steel cylinder with polyester powder coating
- 100% leak detected
- Bursting disc included
- Production under ISO 9001 quality system
- CE, DIN EN 3, MED, GS Mark
- 5 year warranty

Model Number	CO2C	CO5C
Capacity (kg)	2	5
Cylinder Diameter (mm)	105	137
Fire Rating	34B	89B
Extinguisher Weight (kg)	6.74	15.20
Range of Throw (m)	>4	>4
Duration of Discharge (secs)	6	11
Working Pressure (bar) at 20°C	65	65
Test Pressure (bar)	315	315
Operation Temperature (°C)	-30 to +60	-30 to +60
GS Mark	✓	✓
MED Approved	✓	✓
DIN EN 3 Approved	✓	✓
Packing Size (LxWxH) (mm)	560x270x115	785x275x145



## ALUMINIUM CO2 FIRE EXTINGUISHER

### Stored Pressure

- Suitable for class B fires
- CE approved brass valve
- CE approved high tensile aluminium cylinder with polyester powder coating
- 100% leak detected
- Bursting disc included
- Production under ISO 9001 quality system
- CE, DIN EN 3, MED, GS Mark
- 5 year warranty

Model Number	CO2A	CO5A
Capacity (kg)	2	5
Cylinder Diameter (mm)	111	152
Fire Rating	34B	89B
Extinguisher Weight (kg)	5.38	12.55
Range of Throw (m)	>4	>4
Duration of Discharge (secs)	6	15
Working Pressure (bar) at 20°C	60	60
Test Pressure (bar)	250	250
Operation Temperature (°C)	-30 to +60	-30 to +60
GS Mark	✓	✓
MED Approved	✓	✓
DIN EN 3 Approved	✓	✓
Packing Size (LxWxH) (mm)	580x270x120	790x270x165



## MOBILE ABC POWDER FIRE EXTINGUISHER

### Stored Pressure

- Suitable For Class A B C Fires
- Forged nickel-plated brass cylinder valve
- CE approved phosphated steel cylinder with polyester powder coating
- High Performance Dry Chemical Powder According to DIN EN 615
- 100% leak detected
- Pressure Release Valve included
- Production under ISO 9001 quality system
- CE, DIN EN 1866, MED, GS Mark
- 5 year warranty

Model Number	PD50E
Capacity (kg)	50
Cylinder Diameter (mm)	300
Fire Rating	A III B C
Extinguisher Weight (kg)	91.00
Range of Throw (m)	>5
Duration of Discharge (secs)	73
Working Pressure (bar) at 20°C	15
Test Pressure (bar)	30
Operation Temperature (°C)	-30 to +60
GS Mark	✓
MED Approved	✓
DIN EN 1866 Approved	✓
Packing Size (LxWxH) (mm)	440x380x930



## MOBILE ABC POWDER FIRE EXTINGUISHER

### Cartridge Operated

- Suitable For Class A B C Fires
- Forged nickel-plated brass cylinder cap with pressure indicator
- CE approved phosphated steel cylinder with polyester powder coating
- TPED CE Approved Outside N2 Gas Cylinder
- High Performance Dry Chemical Powder According to DIN EN 615
- 100% leak detected
- Bursting disc included
- Production under ISO 9001 quality system
- CE, DIN EN 1866, MED, GS Mark
- 5 year warranty

Model Number	GPD50
Capacity (kg)	50
Cylinder Diameter (mm)	300
Fire Rating	A I V B C
Extinguisher Weight (kg)	94.00
Range of Throw (m)	>5
Duration of Discharge (secs)	78
Working Pressure (bar) at 20°C	10
Test Pressure (bar)	30
Operation Temperature (°C)	-30 to +60
GS Mark	✓
MED Approved	✓
DIN EN 1866 Approved	✓
Packing Size (LxWxH) (mm)	540x380x930





**VICTORY**

**Certified, high-quality fire extinguishers for every application**

**CE-certified portable fire extinguishers and suppression systems.  
Powder, CO2, and Foam options with verified compliance  
for European markets.**

## **VICTORY ZX GmbH**

📍 **Lerchenfeldstr. 72, 47877 Willich-Anrath**

☎ **+49 (0) 2156 914 9977**

🌐 **[www.victoryzx.de](http://www.victoryzx.de)**