

OGS Models

Ozone Gas Systems

All OGS Models Include:
0-100% O₃ Generator Turndown
PID Loop For Precise Process Control
Datalogging For Historical & Real Time System Performance
Customizable E-mail Alert System For Customer And Service Provider

OGS-1

140 g/hr O₃ @ 10%
 210 g/hr O₃ @ 5%
 Single Output Ozone Gas

208VAC, 3Ph, 20A, 60Hz

60"Hx 35"W x 25"D
 ~400 lb

Oxygen Requirement:
 For 140 g/hr:
 40 SCFH @ 20 PSI

Oxygen Requirement:
 For 210 g/hr:
 112 SCFH @ 25 PSI

NEMA 1 -Powder Coated Steel

Compatible with:
 M-200 Aqueous Distribution
 DS-10/20 Gaseous Distribution

Floor Mounted

OGS-2

280 g/hr O₃ @ 10%
 420 g/hr O₃ @ 5%
 Single Output Ozone Gas

208VAC, 3Ph, 30A, 60Hz

60"Hx 48"W x 25"D
 ~550 lb

Oxygen Requirement:
 For 280 g/hr:
 80 SCFH @ 20 PSI

Oxygen Requirement:
 For 420 g/hr:
 225 SCFH @ 25 PSI

NEMA 1 -Powder Coated Steel

Compatible with:
 M-200 Aqueous Distribution
 DS-10/20 Gaseous Distribution

Floor Mounted

OGS-4

560 g/hr O₃ @ 10%
 840 g/hr O₃ @ 5%
 Single Output Ozone Gas

208VAC, 3Ph, 60A, 60Hz

60"Hx 35"W x 25"D
 ~900 lb

Oxygen Requirement:
 For 560 g/hr:
 160 SCFH @ 20 PSI

Oxygen Requirement:
 For 840 g/hr:
 450 SCFH @ 25 PSI

NEMA 1 -Powder Coated Steel

Compatible with:
 M-200 Aqueous Distribution
 DS-10/20 Gaseous Distribution

Floor Mounted