

Extraplana 100 Canto

Acrylic



Perimeter edge 100 mm



25 mm internal depth



Thermoformed acrylic sheet with structural reinforcement



Ø90 mm waste with trap included
(water flow rate at 15 mm: 60 L/m)



Smooth surface



Gloss finish



Floor-mounted installation

Material *Acrylic*

Acrylic is a lightweight and durable material with a smooth finish and a warm touch. The thermoforming process of high-quality acrylic sheets ensures a non-porous surface, comfort of use and high colour stability.



Lightweight and impact-resistant material



Allows seamless monobloc pieces



Non-porous structure with high colour stability



Resistant to humidity and deformation



Warm and pleasant to the touch




Hygienic and water-repellent finish,
allowing easy cleaning

Colour



White



DIMENSIONS AXB (mm)	REFERENCE	C	D	E	INTERNAL DEPTH	NET WEIGHT	VOLUME
800x800	160504108080	330	700	930	25	11,4 kg	820x820x115
900x900	160504109090	450	800	1070	25	12,7 kg	920x920x115
1000x1000	16050410100100	520	900	1220	25	15,1 kg	1020x1020x115

Dimensional tolerance +/- 1%

Cardboard packaging: 1,41 kg/m²

Maintenance

Avoid contact with lacquers, nail polish remover, organic solvents, lit cigarettes or other corrosive products. Do not clean with abrasive scourers. Clean only with water, neutral soap and a soft cloth.

STANDARD: NP EN 14527:2006 + A1 (2013)