

## DISCRIPTION

**TURBO TORQUE LIFE 3** is a high-quality mineral engine oil formulated to provide reliable lubrication and protection for diesel and petrol engines operating under normal service conditions. It helps maintain engine cleanliness and smooth operation in older engine designs.

**TURBO TORQUE LIFE 3** is formulated from carefully selected mineral base oils and a balanced additive system to deliver dependable engine protection, wear control, and resistance to oxidation.

It is designed for use in naturally aspirated diesel engines and older petrol engines where API CC or API SC performance is required.

The formulation helps reduce engine deposits, protects critical engine components against wear, and maintains oil stability during extended operation under moderate operating conditions. Diesel CC/SC is suitable for both on-road and off-road applications, offering consistent performance in a wide range of ambient temperatures when used with the appropriate SAE viscosity grade.

## APPLICATION

**TURBO TORQUE LIFE 3** is recommended for use in:

- Naturally aspirated diesel engines operating under light to moderate duty conditions
- Older petrol engines requiring API SC performance
- Passenger cars, light commercial vehicles, and agricultural equipment
- Industrial engines where a monograde or multigrade CC/SC oil is specified
- Mixed fleet operations where CC/SC specification is required

## BENEFITS

- Good protection against engine wear and corrosion
- Helps control sludge and deposit formation
- Stable performance under normal operating temperatures
- Supports smooth engine operation and reliability
- Suitable for a wide range of older diesel and petrol engines
- Cost-effective lubrication solution for conventional engine designs



**Performance**

<b>API</b>	<b>CC/SC</b>
Caterpillar	CAT TO-2
Allison	C3-C-4

**AVAILABILITY**

SAE Grades 10, 20, 30, 40, 50 and 60.

**Packaging:** 1Q,1L,4Q, 4L,5Q, 5L, 18L, 20L, 25L, Drums, IBC.

**Specification**

Test Parameter	Units	Test Limits	Test Method
SAE Grade	-	30	-
Appearance	-	C&B	Visual
Density @ 15°C	g/cm3	0.872	ASTM D-4052
Viscosity @ 40°C	cSt	70	ASTM D-445
Viscosity @ 100°C	cSt -	9.3-12.4	ASTM D-445
Viscosity Index, min.		110	ASTM D- 2270
Flash Point (COC),min.	°C	232	ASTM D-92
Pour Point, max.	°C	-20	ASTM D-97
Base Number,min.	mg/gr	-18	ASTM D-2896
<b>CODE</b>	-	<b>411/3</b>	-