

## DISCRIPTION

TURBO TORQUE LIFE 2 is a high-quality mineral-based lubricant formulated to provide reliable performance and protection for both diesel and petrol engines operating under moderate to severe service conditions.

TURBO TORQUE LIFE 2 is formulated using carefully selected base oils and a balanced additive system to meet API CD (diesel) and API SG (petrol) performance requirements. It provides effective engine cleanliness, wear protection, and oxidation resistance in naturally aspirated and turbocharged engines operating in warm climates or steady operating conditions.

This oil is suitable for older-generation diesel and gasoline engines where monograde lubricants are recommended. Its stable viscosity characteristics ensure consistent lubrication, reduced oil consumption, and dependable performance under continuous load operations.

## APPLICATION

**TURBO TORQUE LIFE 2** is recommended for use in:

- Naturally aspirated and turbocharged diesel engines requiring API CD performance
- Petrol engines requiring API SG performance
- Commercial vehicles, trucks, buses, and agricultural machinery
- Construction and industrial equipment operating under steady loads
- Stationary engines and generators
- Vehicles and equipment operating in warm climatic conditions

## BENEFITS

- Provides effective protection against engine wear and corrosion
- Helps control oxidation and deposit formation
- Maintains engine cleanliness and reliability
- Suitable for operation with high-sulfur diesel fuel
- Offers good thermal stability under high operating temperatures
- Helps extend engine service life and reduce maintenance costs



**Performance**

<b>API</b>	<b>CD/SG</b>
Caterpillar	CAT TO-2
Allison	C3-C-4

**AVAILABILITY**

SAE Grades 10, 20, 30, 40, 50 and 60.

**Packaging:** 1Q,1L,4Q, 4L,5Q, 5L, 18L, 20L, 25L, Drums, IBC.

**Specification**

Test Parameter	Units	Test Limits	Test Method
SAE Grade	-	<b>30</b>	-
Appearance	-	C&B	Visual
Density @ 15°C	g/cm3	0.864	ASTM D-4052
Viscosity @ 40°C	cSt	78	ASTM D-445
Viscosity @ 100°C	cSt	<b>9.3-12.4</b>	ASTM D-445
Viscosity Index, min.	-	110	ASTM D- 2270
Flash Point (COC),min.	°C	242	ASTM D-92
Pour Point, max.	°C	-18	ASTM D-97
Base Number,min.	mg/gr	8-12	ASTM D-2896
<b>CODE</b>	-	<b>410/3</b>	-