

DISCRIPTION

Ideal Life Plus engine oil is formulated using a premium blend of high-quality synthetic and mineral base oils combined with an advanced additive package. It is designed to deliver reliable protection and performance for modern petrol-powered passenger cars and light commercial vehicles.

The optimized formulation provides strong wear protection, thermal stability, and engine cleanliness under a wide range of driving conditions. Its improved low-temperature fluidity ensures faster oil flow during cold starts while maintaining a stable protective film at normal and high operating temperatures.

APPLICATION

Ideal Life Plus is recommended for use in modern petrol engines, including multi-valve, turbocharged, and high-performance engines where a synthetic technology lubricant is required.

BENEFITS

- Reliable engine performance through effective wear protection and clean operation.
- Improved cold-start lubrication helps reduce engine wear during start-up.
- Enhanced oxidation stability supports cleaner engine operation and reduced deposits.
- Maintains protective oil film strength under varying driving conditions.
- Contributes to improved fuel efficiency in engines designed for lower-viscosity oils.

Performance

- API SN
- ILSAC GF-5
- ACEA A5/B5

Approvals:

API SN

AVAILABILITY

SAE Grades: 0W-16, 0W-20, 5W-20, 0W-30, 5W-30, 10W-30, 0W-40, 5W-40, 10W-40, 0W-50, 5W-50

Packaging: 1L, 4L, 5L, 18L, 20L, 25L, Drums, IBC

Specification

| Test Parameter | Units | Test Limits | Test Method |
|-----------------------|-------|--------------------|--------------|
| SAE Grade | - | 0W50 | - |
| Appearance | - | C&B | Visual |
| Density @ 15°C | g/cm3 | 0.859 | ASTM D-4052 |
| Viscosity @ 40°C | cSt | 118 | ASTM D-445 |
| Viscosity @ 100°C | cSt - | 16.3 – 21.8 | ASTM D-445 |
| Viscosity Index, min. | | 150 | ASTM D- 2270 |
| CCS, max | mPa-S | 6600@-35 | ASTM D-5293 |
| Flash Point min. | °C | 228 | ASTM D-92 |
| Pour Point, max. | °C | -38 | ASTM D-97 |
| TBN, min | mg/g | 8 | ASTM D-2896 |
| Code | - | 100/10 | - |