

DISCRIPTION

TOP GEAR LIFE is a High performance extreme pressure gear oil formulated to provide outstanding protection against wear, shock loading, and high torque conditions in automotive differentials and gear systems. Suitable for hypoid gears operating under severe service conditions.

TOP GEAR LIFE is a premium quality extreme pressure lubricant specially formulated with high quality base oils and advanced sulfur-phosphorus additive technology to provide superior load carrying capability and protection against scuffing, pitting, and wear.

It is designed for hypoid gears and heavily loaded axle drives operating under high speed, high torque, and shock load conditions. The advanced formulation ensures excellent oxidation stability, thermal stability, rust and corrosion protection, and resistance to foam formation.

APPLICATION

TOP GEAR LIFE is recommended for use in

- Hypoid gear differentials
- Rear axles and final drives
- Manual transmissions (where GL-5 is specified)
- Heavy duty trucks and buses
- Construction and agricultural equipment
- Off-highway vehicles
- Passenger cars requiring API GL-5 performance

BENEFITS

- Excellent extreme pressure (EP) protection
- Superior protection against wear and scoring
- High load carrying capability
- Outstanding thermal and oxidation stability
- Protects against rust and corrosion
- Reduces foam formation
- Ensures smooth gear operation
- Extends gear and bearing life

PRODUCT DATA SHEET



Performance

API GL-5

AVAILABILITY

SAE Grade 80W90 , 85W90 And 85W140

Packaging: 1Q,1L,4Q, 4L,5Q, 5L, 18L, 20L, 25L, Drums, IBC.

Specification

Test Parameter	Units	Test Limits	Test Method
SAE Grade		85W90	-
Appearance	-	C&B	Visual
Density @ 15°C	g/cm ³	0.88	ASTM D-4052
Viscosity @ 40°C	cSt	150	ASTM D-445
Viscosity @ 100°C	cSt	13.5 – 18.5	ASTM D-445
Viscosity Index,min.	-	105	ASTM D- 2270
Flash Point(COC), min.	°C	218	ASTM D-92
Pour Point, max.	°C	-22	ASTM D-97
CODE		501/2	-

TOP GEAR LIFE

85W90 GL-5

FULLY SYNTHETIC