

## DISCRIPTION

**TOP ATF LIFE** is a high-performance automatic transmission fluid formulated with high quality base oils and advanced additive technology to deliver improved oxidation stability, enhanced wear protection, and smooth shifting performance. It is designed for automatic transmissions requiring DEXRON® III G performance level.

**TOP ATF LIFE III G** Automatic Transmission Fluid is engineered to provide reliable operation and extended service life in modern automatic transmission systems. Formulated with carefully selected base oils and an advanced additive system, it offers superior thermal stability, excellent friction control, and enhanced resistance to oxidation and deposit formation.

The formulation ensures smooth and consistent gear shifting while protecting transmission components against wear, corrosion, and sludge build-up. Its balanced viscosity characteristics provide dependable performance across a wide temperature range, making it suitable for both normal and severe operating conditions.

## APPLICATION

**TOP ATF LIFE** is recommended for use in

- Automatic transmissions requiring DEXRON® III G performance level
- Power steering systems
- Torque converters
- Hydraulic systems where ATF is specified
- Passenger cars and light commercial vehicles

## BENEFITS

- Smooth and consistent gear shifting
- Excellent oxidation and thermal stability
- Improved wear protection
- Superior friction control
- Good low temperature fluidity
- Protects against rust and corrosion
- Reduced sludge and varnish formation
- Extended service life

## PRODUCT DATA SHEET



### PERFORMANCE

DEXRON III G

### Specification

Test Parameter	Units	Test Limits	Test Method
Appearance	-	C&B	Visual
Color	-	RED	
Density @ 15°C	g/cm <sup>3</sup>	0.87	ASTM D-4052
Viscosity @ 40°C,	cSt	36 - 40	ASTM D-445
Viscosity @ 100°C	cSt	6 - 9	ASTM D-445
Viscosity Index,min.	-	160	ASTM D- 2270
Flash Point(COC), min.	°C	190	ASTM D-92
Pour Point,max.	°C	-40	ASTM D-97
Foaming character	ml/ml	0/0	ASTM D-892
Copper Strip@ 3 hrs/100°C	-	1B	ASTM D-130
CODE		608	

TOP ATF LIFE

DEXRON III G

FULLY SYNTHETIC