

## DISCRIPTION

**DEXRON VI** is a premium fully synthetic automatic transmission fluid formulated with advanced synthetic base oils and high-performance additive technology to provide superior oxidation stability, enhanced wear protection, and smooth shifting performance in modern automatic transmission systems.

**DEXRON VI Fully Synthetic Automatic Transmission Fluid** is engineered to deliver outstanding performance and extended service life in modern automatic transmissions. Formulated with high-quality synthetic base oils and advanced friction modifier technology, it provides excellent thermal stability, superior resistance to oxidation, and improved protection against wear and deposit formation

DEXRON VI Fully Synthetic Automatic Transmission Fluid is engineered to deliver outstanding performance and extended service life in modern automatic transmissions. Formulated with high-quality synthetic base oils and advanced friction modifier technology, it provides excellent thermal stability, superior resistance to oxidation, and improved protection against wear and deposit formation

## APPLICATION

**DEXRON VI** is recommended for use in

- Automatic transmissions requiring GM DEXRON® VI performance level
- Modern 6-speed, 8-speed, and higher automatic transmissions
- Applications requiring low-viscosity ATF
- Power steering systems where specified
- Vehicles operating under severe driving conditions

## BENEFITS

- Ultra-smooth and precise gear shifting
- Outstanding oxidation and thermal stability
- Excellent wear protection for gears and clutches
- Superior friction control performance
- Excellent low-temperature fluidity
- High viscosity stability
- Protects against rust and corrosion
- Extended service interval capability
- Maintains transmission cleanliness

## PRODUCT DATA SHEET



### PERFORMANCE

DEXRON VI FULLY SYNTHETIC

### Specification

Test Parameter	Units	Test Limits	Test Method
Appearance	-	C&B	Visual
Color	-	RED	
Density @ 15°C	g/cm <sup>3</sup>	0.858	ASTM D-4052
Viscosity @ 40°C,	cSt	28 – 32	ASTM D-445
Viscosity @ 100°C	cSt	5.6 – 6.8	ASTM D-445
Viscosity Index,min.	-	175	ASTM D- 2270
Flash Point(COC), min.	°C	190	ASTM D-92
Pour Point,max.	°C	-47	ASTM D-97
Foaming character	ml/ml	0/0	ASTM D-892
Copper Strip@ 3 hrs/100°C	-	1B	ASTM D-130
CODE		610	

DEXRON VI AUTOMATIC  
TRANSMISSION FLUID  
FULLY SYNTHETIC