

DISCRIPTION

TOP ATF LIFE PLUS Synthetic Technology is a premium automatic transmission fluid formulated with high quality synthetic technology base oils and advanced additive systems to deliver superior oxidation stability, smooth shifting performance, and enhanced wear protection. It is designed for modern automatic transmissions requiring DEXRON® III H performance level

TOP ATF LIFE PLUS is a high-performance fluid engineered to provide extended service life and reliable protection under severe operating conditions. Formulated with synthetic technology base oils and a carefully balanced additive system, it delivers outstanding thermal stability, superior friction control, and enhanced resistance to oxidation and deposit formation

This advanced formulation ensures smooth and precise gear shifting while protecting critical transmission components against wear, rust, corrosion, and sludge formation. Its excellent low-temperature fluidity supports fast circulation during cold starts, while its high viscosity stability maintains optimal film strength at elevated operating temperatures.

APPLICATION

TOP ATF LIFE PLUS is recommended for use in

- Automatic transmissions requiring DEXRON® III H performance level
- Power steering systems
- Torque converters
- Hydraulic systems where ATF is specified
- Passenger cars and light commercial vehicles
- Applications operating under high temperature and severe service conditions

BENEFITS

- Smooth, consistent, and precise gear shifting
- Superior oxidation and thermal stability
- Enhanced wear protection for gears and transmission components
- Excellent friction control characteristics
- Outstanding low temperature performance
- High viscosity stability under severe operating conditions
- Protects against rust, corrosion, and sludge formation
- Extended service life compared to conventional ATF

PRODUCT DATA SHEET



PERFORMANCE

DEXRON III H

Specification

Test Parameter	Units	Test Limits	Test Method
Appearance	-	C&B	Visual
Color	-	RED	
Density @ 15°C	g/cm ³	0.87	ASTM D-4052
Viscosity @ 40°C,	cSt	36 - 40	ASTM D-445
Viscosity @ 100°C	cSt	6 - 9	ASTM D-445
Viscosity Index,min.	-	170	ASTM D- 2270
Flash Point(COC), min.	°C	190	ASTM D-92
Pour Point,max.	°C	-41	ASTM D-97
Foaming character	ml/ml	0/0	ASTM D-892
Copper Strip@ 3 hrs/100°C	-	1B	ASTM D-130
CODE		603	

TOP ATF LIFE PLUS
SYNTHETIC TECHNOLOGY DEXRON III H