

## DISCRIPTION

**DEXRON IV** is a premium synthetic technology automatic transmission fluid formulated to provide enhanced oxidation stability, smooth shifting performance, and reliable protection for modern automatic transmission systems.

**DEXRON IV** Automatic Transmission Fluid is engineered to deliver dependable performance in automatic transmissions operating under moderate to severe service conditions. Formulated with high-quality synthetic technology base oils and advanced additive systems, it provides improved thermal stability, enhanced wear protection, and stable friction characteristics.

The formulation ensures smooth gear engagement and protects transmission components against wear, corrosion, and deposit formation. Its balanced viscosity characteristics allow reliable performance across a wide temperature range, making it suitable for modern passenger cars and light commercial vehicles.

## APPLICATION

**DEXRON IV** is recommended for use in

- Automatic transmissions requiring enhanced ATF performance
- Applications previously requiring Dexron III type fluids
- Power steering systems
- Torque converters
- Hydraulic systems where ATF-type fluid is specified

## BENEFITS

- Smooth and consistent shifting performance
- Improved oxidation resistance
- Enhanced wear protection
- Excellent friction stability
- Good low-temperature fluidity
- Protects against rust and corrosion
- Extended service life compared to conventional ATF

## PRODUCT DATA SHEET



### PERFORMANCE

DEXRON IV

### Specification

Test Parameter	Units	Test Limits	Test Method
Appearance	-	C&B	Visual
Color	-	RED	
Density @ 15°C	g/cm <sup>3</sup>	0.858	ASTM D-4052
Viscosity @ 40°C,	cSt	28 – 32	ASTM D-445
Viscosity @ 100°C	cSt	5.6 – 6.8	ASTM D-445
Viscosity Index,min.	-	160	ASTM D- 2270
Flash Point(COC), min.	°C	190	ASTM D-92
Pour Point,max.	°C	-44	ASTM D-97
Foaming character	ml/ml	0/0	ASTM D-892
Copper Strip@ 3 hrs/100°C	-	1B	ASTM D-130
CODE		604	

DEXRON IV AUTOMATIC  
SYNTHETIC TECHNOLOGY TRANSMISSION FLUID