

DISCRIPTION

POWER BOAT LIFE is a high-performance four-stroke engine lubricant specially formulated for modern marine engines. It provides excellent protection against wear, rust, and corrosion while ensuring reliable engine performance in both freshwater and saltwater environments.

POWER BOAT LIFE is a premium quality four-stroke lubricant designed to meet the performance requirements of modern marine engines operating under severe conditions. It is formulated with high-quality base oils and advanced additive technology to deliver excellent engine protection, improved oxidation stability, and superior resistance to rust and corrosion caused by moisture and saltwater exposure.

This oil helps maintain engine cleanliness by minimizing sludge and deposit formation while providing excellent wear protection for critical engine components. Its advanced formulation ensures reliable lubrication, enhanced engine durability, and smooth operation even under heavy loads and high operating temperatures

APPLICATION

POWER BOAT LIFE is recommended for use in

- Four-stroke marine outboard engines
- Four-stroke inboard marine engines
- Personal watercraft requiring four-stroke engine oil
- Marine engines operating in freshwater or saltwater environments
- High-performance marine engines requiring API SL / NMMA FC-W specification lubricants

BENEFITS

- Excellent protection against engine wear and scuffing
- Superior resistance to rust and corrosion in marine environments
- Outstanding oxidation stability for extended engine life
- Helps prevent sludge and deposit formation
- Maintains engine cleanliness and piston protection
- Provides reliable lubrication under heavy loads and high temperatures
- Enhances engine durability and performance

POWER BOAT LIFE

FULLY SYNTHETIC 10W40 SL/FCW (4T)

PRODUCT DATA SHEET



Performance

- API SL
- NMMA FC-W

AVAILABILITY

SAE Grades 5W40, 10W30, 10W40, 15W40, 20W40, 15W50 and 20W50.

Packaging: 1Q, 1L, 4Q, 4L, 5Q, 5L, 18L, 20L, 25L, Drums, IBC.

Specification

Test Parameter	Units	Test Limits	Test Method
SAE Grade	-	10W40	-
Appearance	-	C&B	Visual
Density @ 15°C	g/cm ³	0.863	ASTM D-4052
Viscosity @ 40°C	cSt	92	ASTM D-445
Viscosity @ 100°C	cSt	12.5– 16.2	ASTM D-445
Viscosity Index, min.	-	135	ASTM D- 2270
Flash Point min.	°C	220	ASTM D-92
Pour Point, max.	°C	-26	ASTM D-97
TBN, min	mg/g	6	ASTM D-2896
Code	-	202/3	-